



PCB.焊接图
PCB.WELDING DRAWING

NOTES:

- 1.Rat voltage: 50mA DC12V
1.额定电流:50mA DC12V
- 2.Contact Resistance:≤100mΩ
2.接触电阻: ≤100mΩ
- 3.Travel: 0.25±0.1mm
3.行程: 0.25 + 0.1mm

- 4.Insulation Resistance:≥100MΩ
4.绝缘电阻: ≥100MΩ
- 5.Dielectric strength: ≥250VAC
5.介电强度: ≥250VAC
- 6.Life: 200,000 times
6.寿命: 200,000 times
- 7.Operating Temperature:-20 to ~80℃
7.使用温度: -20 to ~80℃



电路图
CIRCUIT DRAGRAM

TP1292 □ □ □ □




Height

Actuation Force

16 : 160gf

26 : 260gf

Height	
11	4.3MM
12	4.5MM
125	12.5MM
13	5.0MM
14	5.5MM
15	6.0MM
155	15.5MM
16	6.5MM
17	7.0MM
18	7.5MM



5	Push-button 按钮	PPA	1	Black 黑色
4	Blind flange 盖板	Iron cover plate 铁盖板	1	Copper tin plating 镀铜锡
3	Shrapnel 弹片	SUS	1	Ag plating 镀银
2	Noumenon 本体	PPA	1	Black 黑色
1	Card 卡件	Brass	1	Ag plating 镀银
NO 序号	Part name 部件名	Material 材料	QTY 数量	Remark 备注

A4				
A3				
A2				
A1				
REV	DATE	REVISION	DESCRIPTION	ISSUE



COMMON TOLERANCE	
X.XX	± 0.10
X.X	± 0.15
X	± 0.25
ANGULAR	—

UNIT	MM	PROJECTED	PRODUCT NAME: TP1292 □ □ □ □
DRAWN BY	SHUHAO	CHECKED BY	COCO
DATE	2019	APPROVAL B	ALEN
MODEL NO:		Https: www.rocpcu.tw	
ROCPCU TECHNOLOGY CO.,LTD			
Copies are issued in strict confidence and shall not be reproduced or copied, or used as the basic of manufacture or sale of apparatus without permission			