


A4				
A3				
A2				
A1				
REV	DATE	REVISION	DESCRIPTION	ISSUE



COMMON TOLERANCE	
X.XX	± 0.10
X.X	± 0.15
X	± 0.25
ANGULAR	—



UNIT	MM	PROJECTED	
DRAWN BY	SHUHAO	CHECKED BY	COCO
DATE	2019	APPROVAL	B ALEN
ROCPCU TECHNOLOGY CO.,LTD			
Copies are issued in strict confidence and shall not be reproduced or copied, or used as the basic of manufacture or sale of apparatus without permission			

PRODUCT NAME:	
MODEL NO:	TP992506G <input type="checkbox"/> <input type="checkbox"/>
Https:	www.rocpcu.tw

	A	B	C	D	E	F	G		
1	<div style="display: flex; justify-content: space-around; align-items: center;"> <div style="text-align: center;"> <p>TP992506G <input type="checkbox"/> <input type="checkbox"/></p> <p>Operation method</p> <p>1:Self-locking 2:Self-compound</p> </div> <div style="text-align: center;"> <p>Material</p> <p>A: Aluminum alloy S: Stainless steel B: Brass</p> </div> </div>								
2	<div style="display: flex; justify-content: space-between;"> <div style="width: 45%;"> <p>性能参数</p> <ol style="list-style-type: none"> Heating current: Ui: AC250V, Ith: 20A 发热电流: Ui: AC250V, Ith: 20A Rated current:16A/AC110V/220V 16A/DC12V/24V 额定电流:16A/AC110V/220V 16A/DC12V/24V Power-frequency withstand voltage:1500V1min 工频耐压:1500V1min Insulation resistance:≥1000MΩ 绝缘电阻 :≥1000MΩ Contact resistance:≤50mΩ 接触电阻 :≤50mΩ Pressing stroke:3.50mm ± 0.10 按压行程:3.50mm ± 0.10 Contact stroke:1.35mm±0.10 接触行程 :1.35mm±0.10 </div> <div style="width: 45%;"> <p>连接形式</p> <ol style="list-style-type: none"> Welding temperature of wire: 320 ± 20 °C 线材焊接温度: 320±20°C Wire welding duration: less than 3 seconds 线材焊接时长: 时长3秒以下 Can be used with dedicated connectors: 可配专用接插件使用: Switch function wire: blue wire NO (1²mm) 开关功能线材: 蓝线NO (1²mm) </div> </div>								
3	<ol style="list-style-type: none"> Nut assembly torque:5-14N 螺帽装配力矩:5-14N Protection level:IP67 防护等级:IP67 Explosion prevention level: IK10 防暴等级: IK10 Working environment temperature: -20 °C~+55 °C 工作环境温度: -20 °C~+55 °C Compression torque: ≤ 4N 按压扭力: ≤4N Electrical life: 30000 cycles 电气寿命: 30000 cycles mechanical: 200000cycles 机械寿命: 200000cycles NO reverse thrust foot torque: ≤30N NO反推脚扭力: ≤30N 								
4									
5	A4				UNIT	MM	PROJECTED		PRODUCT NAME:
	A3				DRAWN BY	SHUHAO	CHECKED BY	COCO	MODEL NO:TP992506G <input type="checkbox"/> <input type="checkbox"/>
	A2				DATE	2019	APPROVAL B	ALEN	Https: www.rocpu.tw
	A1				ROCPU TECHNOLOGY CO.,LTD				
	REV	DATE	REVISION	DESCRIPTION	ISSUE	Copies are issued in strict confidence and shall not be reproduced or copied,or used as the basic of manufacture or sale of apparatus without permission			
	A	B	C	D	E	F	G		



COMMON TOLERANCE	
X.XX	± 0.10
X.X	± 0.15
X	± 0.25
ANGULAR	—

A	B	C	D	E	F	G
材质参数						
1						
2	8	Base 底座	PBT	1		
3	7	Pin 引脚	Brass 黄铜	1	Silvering 镀银	
4	6	Contact material 接触材质	silver alloy 银合金	1		
5	5	Bush 衬套	PBT	1		
6	4	Arm nut 固定螺帽	Brass 黄铜	1	nickeling 镀镍	
7	3	Oring O型圈	Silica gel 硅胶	1		
8	2	Housing 外壳	SUS/Aluminum alloy/Brass 不锈钢/铝合金/黄铜	1		
9	1	Key 按键	SUS/Aluminum alloy/Brass 不锈钢/铝合金/黄铜	1		
	NO 序号	Part name 部件名	Material 材料	QTY 数量	Remark 备注	
A4				UNIT	MM	PROJECTED 
A3				DRAWN BY	SHUHAO	CHECKED BY
A2				DATE	2019	APPROVAL B
A1						ALEN
REV	DATE	REVISION	DESCRIPTION	ISSUE	 ROCPCU	
COMMON TOLERANCE			X.XX	± 0.10	PRODUCT NAME: MODEL NO:TP992506G□□	
			X.X	± 0.15	Https: www.rocpcu.tw	
			X	± 0.25	ROCPCU TECHNOLOGY CO.,LTD	
			ANGULAR	—		
Copies are issued in strict confidence and shall not be reproduced or copied, or used as the basic of manufacture or sale of apparatus without permission						