

A4				
A3				
A2				
A1				
REV	DATE	REVISION	DESCRIPTION	ISSUE





COMMON TOLERANCE

X.XX	± 0.10
X.X	± 0.15
X	± 0.25



ANGULAR

UNIT	MM	PROJECTED	
DRAWN BY	FUYUAN	CHECKED BY	COCO
DATE	2019	APPROVAL	B ALEN
ROCPCU TECHNOLOGY CO.,LTD			

PRODUCT NAME:	
MODEL NO:	TP91206G <input type="checkbox"/> <input type="checkbox"/>
Https:	www.rocpcu.tw
<small>Copies are issued in strict confidence and shall not be reproduced or copied, or used as the basic of manufacture or sale of apparatus without permission</small>	

	A	B	C	D	E	F	G				
1	<p>TP91206G <input type="checkbox"/> <input type="checkbox"/></p> <p>Operation method <input type="checkbox"/> Material <input type="checkbox"/></p> <p>1:Self-locking 2:Self-compound</p> <p>A: Aluminum alloy S: Stainless steel B: Brass</p>										
2											
3	<p>性能参数</p> <table border="0"> <tr> <td style="vertical-align: top;"> <p>1. Heating current: Ui: AC250V, Ith: 3A 发热电流: Ui: AC250V, Ith: 3A</p> <p>2. Rated current:2A/DC36V 额定电流:2A/DC36V</p> <p>3. Insulation resistance:≥1000MΩ 绝缘电阻 ≥1000MΩ</p> <p>4. Contact resistance:≤50mΩ 接触电阻 :≤50mΩ</p> <p>5. Pressing stroke:2.30mm ± 0.10 按压行程:2.30mm ± 0.10</p> <p>6. Contact stroke:1.00mm±0.10 接触行程 :1.00mm±0.10</p> <p>7. welding temperature: 320 °C± 20 °C 焊接温度: 320 °C± 20 °C</p> <p>8. Welding duration: Less than 3 seconds in duration 焊接时长: Less than 3 seconds in duration</p> </td> <td style="vertical-align: top;"> <p>9. Nut assembly torque:5-14N 螺帽装配力矩:5-14N</p> <p>10. Protection level:IP65 防护等级:IP65</p> <p>11. Explosion prevention level: IK08 防暴等级: IK08</p> <p>12. Working environment temperature: -20 °C~+55 °C 工作环境温度: -20 °C~+55 °C</p> <p>13. Compression torque: ≤ 3N 按压扭力: ≤3N</p> <p>14. Electrical life: 500000 cycles 电气寿命: 500000 cycles</p> <p>15. mechanical: 500000cycles 机械寿命: 500000cycles</p> <p>16. NO reverse thrust foot torque: ≤30N NO反推脚扭力: ≤30N</p> </td> </tr> </table>							<p>1. Heating current: Ui: AC250V, Ith: 3A 发热电流: Ui: AC250V, Ith: 3A</p> <p>2. Rated current:2A/DC36V 额定电流:2A/DC36V</p> <p>3. Insulation resistance:≥1000MΩ 绝缘电阻 ≥1000MΩ</p> <p>4. Contact resistance:≤50mΩ 接触电阻 :≤50mΩ</p> <p>5. Pressing stroke:2.30mm ± 0.10 按压行程:2.30mm ± 0.10</p> <p>6. Contact stroke:1.00mm±0.10 接触行程 :1.00mm±0.10</p> <p>7. welding temperature: 320 °C± 20 °C 焊接温度: 320 °C± 20 °C</p> <p>8. Welding duration: Less than 3 seconds in duration 焊接时长: Less than 3 seconds in duration</p>	<p>9. Nut assembly torque:5-14N 螺帽装配力矩:5-14N</p> <p>10. Protection level:IP65 防护等级:IP65</p> <p>11. Explosion prevention level: IK08 防暴等级: IK08</p> <p>12. Working environment temperature: -20 °C~+55 °C 工作环境温度: -20 °C~+55 °C</p> <p>13. Compression torque: ≤ 3N 按压扭力: ≤3N</p> <p>14. Electrical life: 500000 cycles 电气寿命: 500000 cycles</p> <p>15. mechanical: 500000cycles 机械寿命: 500000cycles</p> <p>16. NO reverse thrust foot torque: ≤30N NO反推脚扭力: ≤30N</p>		
<p>1. Heating current: Ui: AC250V, Ith: 3A 发热电流: Ui: AC250V, Ith: 3A</p> <p>2. Rated current:2A/DC36V 额定电流:2A/DC36V</p> <p>3. Insulation resistance:≥1000MΩ 绝缘电阻 ≥1000MΩ</p> <p>4. Contact resistance:≤50mΩ 接触电阻 :≤50mΩ</p> <p>5. Pressing stroke:2.30mm ± 0.10 按压行程:2.30mm ± 0.10</p> <p>6. Contact stroke:1.00mm±0.10 接触行程 :1.00mm±0.10</p> <p>7. welding temperature: 320 °C± 20 °C 焊接温度: 320 °C± 20 °C</p> <p>8. Welding duration: Less than 3 seconds in duration 焊接时长: Less than 3 seconds in duration</p>	<p>9. Nut assembly torque:5-14N 螺帽装配力矩:5-14N</p> <p>10. Protection level:IP65 防护等级:IP65</p> <p>11. Explosion prevention level: IK08 防暴等级: IK08</p> <p>12. Working environment temperature: -20 °C~+55 °C 工作环境温度: -20 °C~+55 °C</p> <p>13. Compression torque: ≤ 3N 按压扭力: ≤3N</p> <p>14. Electrical life: 500000 cycles 电气寿命: 500000 cycles</p> <p>15. mechanical: 500000cycles 机械寿命: 500000cycles</p> <p>16. NO reverse thrust foot torque: ≤30N NO反推脚扭力: ≤30N</p>										
4											
5	A4										
	A3										
	A2										
	A1										
	REV	DATE	REVISION DESCRIPTION	ISSUE							
					COMMON TOLERANCE	UNIT	MM	PROJECTED		PRODUCT NAME:	
					X.XX	± 0.10	DRAWN BY	FUYUAN	CHECKED BY	COCO	MODEL NO: TP91206G <input type="checkbox"/> <input type="checkbox"/>
					X.X	± 0.15	DATE	2019	APPROVAL B	ALEN	Https: www.rocpcu.tw
					X	± 0.25	<h1>ROCPCU TECHNOLOGY CO.,LTD</h1>				
					ANGULAR	—	<small>Copies are issued in strict confidence and shall not be reproduced or copied, or used as the basic of manufacture or sale of apparatus without permission</small>				
	A	B	C	D	E	F	G				

NO 序号	Part name 部件名	Material 材料	QTY 数量	Remark 备注
10				
9				
8	Base 底座	PA66	1	
7	Pin 引脚	Brass 黄铜	1	gold-plating 镀金
6	Contact material 接触材质	Silvering 镀银	1	
5	Base 基座	PA66	1	
4	Arm nut 固定螺帽	Brass 黄铜	1	nickeling 镀镍
3	Oring O型圈	Silica gel 硅胶	1	
2	Housing 外壳	SUS/Aluminum alloy/Brass 不锈钢/铝合金/黄铜	1	
1	Key 按键	SUS/Aluminum alloy/Brass 不锈钢/铝合金/黄铜	1	

A4				 台普 ROCPCU	COMMON TOLERANCE		UNIT	MM	PROJECTED		PRODUCT NAME:
A3					X.XX	± 0.10	DRAWN BY	FUYUAN	CHECKED BY	COCO	MODEL NO: TP91206G <input type="checkbox"/> <input type="checkbox"/>
A2					X.X	± 0.15	DATE	2019	APPROVAL B	ALEN	Https: www.rocpu.tw
A1					X	± 0.25	ROCPCU TECHNOLOGY CO.,LTD				
REV	DATE	REVISION	DESCRIPTION		ISSUE	ANGULAR					