







A4					 台普 ROCPCU	COMMON TOLERANCE		UNIT	MM	PROJECTED		PRODUCT NAME:	
A3						X.XX	± 0.10	DRAWN BY	SHUHAO	CHECKED BY	COCO	MODEL NO: TP92229P <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	
A2						X.X	± 0.15	DATE	2019	APPROVAL	B	ALLEN	Https: www.rocpcu.tw
A1						X	± 0.25	<h1>ROCPCU TECHNOLOGY CO., LTD</h1>					
REV	DATE	REVISION	DESCRIPTION	ISSUE		ANGULAR	—						<small>Copies are issued in strict confidence and shall not be reproduced or copied, or used as the basic of manufacture or sale of apparatus without permission</small>
	A		B		C		D	E	F	G			

	A	B	C	D	E	F	G				
1	TP92229P <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>										
2	Operation method 1:Self-locking 2:Self-compound		Material A: Aluminum alloy S: Stainless steel B: Brass	LED voltage 3: 3V 6: 6V 12: 12V 24: 24V 36: 36V 48: 48V 60: 60V 110: 110V 220: 220V							
3	性能参数 1. Rated current:0.1A/DC36V 额定电流:0.1A/DC36V 2. Insulation resistance:≥50MΩ 绝缘电阻 :≥50MΩ 3. Contact resistance:≤50mΩ 接触电阻 :≤50mΩ 4. Pressing stroke:0.50mm ± 0.10 按压行程:0.50mm ± 0.10 5. Contact stroke:0.50mm±0.10 接触行程 :0.50mm±0.10 6. welding temperature: 320 ℃± 20 ℃ 焊接温度: 320 ℃± 20 ℃ 7. Welding duration: Less than 3 seconds in duration 焊接时长: Less than 3 seconds in duration 8. Nut assembly torque:5-14N 螺帽装配力矩:5-14N 9. Protection level:IP67			LED Color R:Red Y:Yellow G:Green B:Blue W:White O:Orange							
4				防护等级:IP67 10. Explosion prevention level: IK08 防暴等级: IK08 11. Working environment temperature: -20 ℃~+55 ℃ 工作环境温度: -20 ℃~+55 ℃ 12. Compression torque: ≤3N 按压扭力: ≤3N 13. Electrical life: 200000 cycles 电气寿命: 200000 cycles 14. mechanical: 1000000cycles 机械寿命: 1000000cycles 15. NO reverse thrust foot torque: ≤30N NO反推脚扭力: ≤30N 16. LED lamp power consumption: 20m以下 LED灯功耗: 20m以下 17. LED lamp lifespan: 40000h LED寿命: 40000h							
5	A4										
	A3										
	A2										
	A1										
	REV	DATE	REVISION DESCRIPTION	ISSUE							
					COMMON TOLERANCE	UNIT	MM	PROJECTED		PRODUCT NAME:	
					X.XX	± 0.10	DRAWN BY	SHUHAO	CHECKED BY	COCO	MODEL NO: TP92229P <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>
					X.X	± 0.15	DATE	2019	APPROVAL B	ALEN	Https: www.rocpcu.tw
					X	± 0.25	ROCPCU TECHNOLOGY CO.,LTD				
					ANGULAR	—					
	A	B	C	D	E	F	G				

NO 序号	Part name 部件名	Material 材料	QTY 数量	Remark 备注
1	Key 按键	SUS/Aluminum alloy/Brass 不锈钢/铝合金/黄铜	1	
2	Housing 外壳	SUS/Aluminum alloy/Brass 不锈钢/铝合金/黄铜	1	
3	Oring O型圈	Silica gel 硅胶	1	
4	Arm nut 固定螺帽	Brass 黄铜	1	nickeling 镀镍
5	Base 基座	PBT	1	
6	Pin 引脚	Brass 黄铜	1	gold-plating 镀金
7	luminous zone 发光区	PC 塑料	1	
8	LEDpin LED脚	Brass 黄铜	1	Silvering 镀银

材质参数

A4				 台普 ROCPCU	COMMON TOLERANCE		UNIT	MM	PROJECTED		PRODUCT NAME:
A3					X.XX	± 0.10	DRAWN BY	SHUHAO	CHECKED BY	COCO	MODEL NO: TP92229P□□□□
A2					X.X	± 0.15	DATE	2019	APPROVAL B	ALEN	Https: www.rocpu.tw
A1					X	± 0.25	ROCPCU TECHNOLOGY CO.,LTD				
REV	DATE	REVISION	DESCRIPTION		ISSUE	ANGULAR					