



NOTES:

- | | |
|--|--|
| 1. Rating: DC30V 100mA | 6. Electrical Life: 100,000 cycles |
| 1. 额定值: DC30V 100mA | 6. 电气寿命: 100000次循环 |
| 2. Contact Resistance: 500mΩ Max | 7. Mechanical Life: 300,000 cycles |
| 2. 接触电阻: 最大500mΩ | 7. 机械寿命: 300000次循环 |
| 3. Insulation Resistance: > 100MΩ DC500V | 8. Ambient Temper Used: -25°C to + 85°C |
| 3. 绝缘电阻: > 100MΩ DC500V | 8. 使用的环境温度: -25°C至 + 85°C |
| 4. Withstand Voltage: AC500V 1min | 9. Ambient Humidity Used: ≤85% at + 40°C |
| 4. 耐压: AC500V 1min | 9. 使用的环境湿度: ≤85% at + 40°C |
| 5. Soldering Temper: 235±5°C 5s | 10. Operating Force: 50gf MAX |
| 5. 钎焊温度: 235±5°C 5s | 10. 操作力: 50gf MAX |

	pressing handle 压柄	SUS	1	
	Contact 触点	silver alloy	1	
5	Terminal 端子	Brass	1	Ag plating 镀银
4	Shrapnel 弹片	Brass	1	
3	Button 按钮	PBT	1	
2	Upper cover 上盖	PBT	1	
1	Pedestal 基座	PBT	1	
NO 序号	Part name 部件名	Material 材料	QTY 数量	Remark 备注

A4				
A3				
A2				
A1				
REV	DATE	REVISION	DESCRIPTION	ISSUE



COMMON TOLERANCE	
X.XX	± 0.10
X.X	± 0.15
X	± 0.25
ANGULAR	—

UNIT	MM	PROJECTED		PRODUCT NAME:
DRAWN BY	FUYUAN	CHECKED BY	COCO	MODEL NO: TP308-21250
DATE	2019	APPROVAL B	ALEN	Https: www.rocpcu.tw
ROCPCU TECHNOLOGY CO.,LTD				
Copies are issued in strict confidence and shall not be reproduced or copied, or used as the basic of manufacture or sale of apparatus without permission				