



- NOTES:
1. Rating: 3A 125VAC
  1. 额定值: 3A 125VAC
  2. Dielectric Strength: AC500 1min
  2. 耐电压: AC500 1min
  3. Contact Resistance: ≤100mΩ Max
  3. 接触电阻: ≤100mΩ
  4. Insulation Resistance: ≥100MΩ
  4. 绝缘电阻: ≥100MΩ
  5. Operating Force: 30±15gf
  5. 操作力: 30±15gf
  6. Electric Life: 100,000 times
  6. 电气寿命: 100,000 times
  7. Mechanical Life: 1,000,000 times
  7. 机械寿命: 1,000,000 times
  8. Operating Temperature: -25 to +85°C
  8. 使用温度: -25 to +85°C

6	Terminal 端子	Barss	1	Ag plating 镀银
5	Contact 触点	silver alloy 银合金	1	
4	Button 按钮	PBT	1	
3	Shrapnel 弹片	Beryllium Copper 铍铜	1	
2	Cover plate 盖片	PBT	1	
1	Pedestal 基座	PBT	1	
NO 序号	Part name 部件名	Material 材料	QTY 数量	Remark 备注

A4					COMMON TOLERANCE X.XX ± 0.10 X.X ± 0.15 X ± 0.25 ANGULAR —	UNIT	MM	PROJECTED		PRODUCT NAME:
A3						DRAWN BY	FUYUAN	CHECKED BY	COCO	MODEL NO: TP30131000
A2						DATE	2019	APPROVAL B	ALEN	Https: www.rocpcu.tw
A1						<b>ROCPCU TECHNOLOGY CO., LTD</b>				
REV	DATE	REVISION	DESCRIPTION			ISSUE	Copies are issued in strict confidence and shall not be reproduced or copied, or used as the basic of manufacture or sale of apparatus without permission			
	A		B		C	D	E	F	G	