



NOTES:

- 1.额定电压: 12VDC 50mA
- 2.接触电阻: ≤100mΩ Max
- 3.行程: 0.25±0.1mm
- 4.绝缘电阻: ≥100MΩ

5.介电强度: ≥250VAC

- 6.寿命: 30,000 times
- 7.使用温度: -20°C±80°C

TP1182 □ □ □ □

Height
Actuation Force
16 : 160gf
26 : 260gf

Height	
15	1.5MM
16	1.6MM
17	1.7MM
20	2.0MM
25	2.5MM

5	Push-Button 按钮	PPA	1	Black 黑色
4	Blind flange 盖板	SUS	1	
3	Shrapnel 弹片	SUS	1	Ag plating 镀银
2	Noumenon 本体	PPA	1	Black 黑色
1	Card 卡件	Brass	1	Ag plating 镀银
NO 序号	Part name 部件名	Material 材料	QTY 数量	Remark 备注

A4				
A3				
A2				
A1				
REV	DATE	REVISION	DESCRIPTION	ISSUE



COMMON TOLERANCE	
X.XX	± 0.10
X.X	± 0.15
X	± 0.25
ANGULAR	

UNIT	MM	PROJECTED		PRODUCT NAME: TP1182 □ □ □ □
DRAWN BY	SHUHAO	CHECKED BY	COCO	MODEL NO:
DATE	2019	APPROVAL B	ALEN	Https: www.rocpcu.tw
ROCPCU TECHNOLOGY CO.,LTD				
Copies are issued in strict confidence and shall not be reproduced or copied, or used as the basic of manufacture or sale of apparatus without permission				