




Technical parameter

技术参数

- Rated current: 100mA 30V DC
1.额定电流: 100mA 30V DC
- Contact resistance: ≤ 200m Ω
2.接触电阻: ≤200m Ω
- Operating force: 260gf ± 50gf
3.操作力: 260gf±50gf
- Maximum stroke: 2.3 ± 0.2mm
4.最大行程: 2.3±0.2mm

5. Operating temperature: -40℃ ~ + 80℃

- 工作温度: -40℃ ~ + 80℃
- Insulation resistance: ≥ 100M Ω
6.绝缘电阻: ≥100MΩ
- Electric strength: AC250v 50Hz 1Min
7.抗电强度: AC250v 50Hz 1Min
- Service life: 10000 times
8.寿命: 10000次
- Switch similar: Self locking
9.开关类似: 自锁





FREE

PUSH

BTSA-□-P-11

Operation
L : self-locking
N : lock-free



7	crochet hook 钩针	SUS 不锈钢丝	1	Natural color 本色
6	Spring 弹簧	SUS 不锈钢丝	1	Natural color 本色
5	reed 簧片	Composite silver 复合银	1	Natural color 本色
4	Upper cover 上盖	PA66 尼龙66	1	transparent 透明
3	handle 按柄	PA66 尼龙66	1	blue 蓝色
2	terminal 端子	Brass 黄铜	1	Natural color/silver 本色/镀银
1	Pedestal 基座	PA66 尼龙66	1	black 黑色
ITEM	Name	Materials	NUM	COLOR

A4				
A3				
A2				
A1				
REV	DATE	REVISION	DESCRIPTION	ISSUE



COMMON TOLERANCE	
X.XX	± 0.10
X.X	± 0.15
X	± 0.25
ANGULAR	—

UNIT	MM	PROJECTED		PRODUCT NAME: BTSA-□-P-11
DRAWN BY	SHUHAO	CHECKED BY	COCO	MODEL NO:
DATE	2019	APPROVAL B	ALEN	Https: www.rocpcu.tw
ROCPCU TECHNOLOGY CO.,LTD				
Copies are issued in strict confidence and shall not be reproduced or copied, or used as the basic of manufacture or sale of apparatus without permission				