







A4					 台普 ROCPCU	COMMON TOLERANCE		UNIT	MM	PROJECTED		PRODUCT NAME:	
A3						X.XX	± 0.10	DRAWN BY	SHUHAO	CHECKED BY	COCO	MODEL NO: TP94008P <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	
A2						X.X	± 0.15	DATE	2019	APPROVAL	B	ALLEN	Https: www.rocpcu.tw
A1						X	± 0.25	<h1>ROCPCU TECHNOLOGY CO.,LTD</h1>					
REV	DATE	REVISION	DESCRIPTION	ISSUE		ANGULAR	—						<small>Copies are issued in strict confidence and shall not be reproduced or copied, or used as the basic of manufacture or sale of apparatus without permission</small>

	A	B	C	D	E	F	G				
1	<p>TP94008P <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/></p> <p>Operation method</p> <p>1:Self-locking 2:Self-compound</p> <p>LED voltage</p> <p>3:3V 6:6V 12:12V 24:24V 36:36V 48:48V 60:60V 110:110V 220:220V</p> <p>Material</p> <p>A: Aluminum alloy S: Stainless steel B: Brass</p> <p>LED Color</p> <p>R:Red Y:Yellow G:Green B:Blue W:White O:Orange</p>			<p>连接形式</p> <ol style="list-style-type: none"> Welding temperature of wire: 320 ± 20 °C 线材焊接温度: 320±20°C Wire welding duration: less than 3 seconds 线材焊接时长: 时长3秒以下 Can be used with dedicated connectors: 可配专用接插件使用: <ol style="list-style-type: none"> Switch function wire: Green Line (C) Blue Line (NO) Yellow Line (NC) 开关功能线材: 绿线 (C) 蓝线 (NO) 黄线 (NC) LED functional wire: red wire positive pole black wire negative pole LED功能线材: 红线正极 黑线负极 LED is an electrodeless lamp bead that can be lit without the need to separate positive and negative poles LED为无极灯珠, 无需分正负极也可点亮 				1			
2								2			
3	<p>性能参数</p> <ol style="list-style-type: none"> Heating current: Ui: AC250V, Ith: 5A 发热电流: Ui: AC250V, Ith: 5A Rated current:3A/DC36V 额定电流:3A/DC36V Power-frequency withstand voltage:2000V/1min 工频耐压:2000V/1min Insulation resistance:≥1000MΩ 绝缘电阻 :≥1000MΩ Contact resistance:≤50mΩ 接触电阻 :≤50mΩ Pressing stroke:2.50mm ± 0.10 按压行程:2.50mm ± 0.10 Contact stroke:1.50mm±0.10 接触行程 :1.50mm±0.10 welding temperature: 320 °C± 20 °C 焊接温度: 320 °C± 20 °C Welding duration: Less than 3 seconds in duration 焊接时长: Less than 3 seconds in duration Nut assembly torque:5-14N.m 螺帽装配力矩:5-14N.m 			<ol style="list-style-type: none"> Protection level:IP67 防护等级:IP67 Explosion prevention level: IK10 防暴等级: IK10 Working environment temperature: -20 °C~+55 °C 工作环境温度: -20 °C~+55 °C Compression torque: ≤2.5N 按压扭力: ≤2.5N Electrical life: 50,000 cycles 电气寿命: 50,000 cycles Mechanical: 500, 000cycles 机械寿命: 500,000cycles LED lamp power consumption: 20mA以下 LED灯功耗: 20mA以下 LED lamp lifespan: 40000h LED寿命: 40000h NO reverse thrust foot torque: ≤30N NO反推脚扭力: ≤30N 				3			
4								4			
5	A4			 <p>台普 ROCPCU</p>	COMMON TOLERANCE	UNIT	MM	PROJECTED		PRODUCT NAME:	5
	A3				X.XX	± 0.10	DRAWN BY	SHUHAO	CHECKED BY	COCO	MODEL NO:TP94008P <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>
	A2				X.X	± 0.15	DATE	2019	APPROVAL B	ALEN	Https: www.rocpcu.tw
	A1				X	± 0.25	<p>ROCPCU TECHNOLOGY CO.,LTD</p> <p>Copies are issued in strict confidence and shall not be reproduced or copied,or used as the basic of manufacture or sale of apparatus without permission</p>				
	REV	DATE	REVISION DESCRIPTION		ISSUE	ANGULAR					
	A	B	C	D	E	F	G				

A		B		C		D		E		F		G	
材质参数													
1	9	luminous zone 发光区		PC 塑胶		1							
	8	LEDpin LED引脚		Brass 黄铜		1		Silvering 镀银					
2	7	Base 底座		PA46		1							
	6	NOPin NO引脚		Brass 黄铜		1		gold-plating 镀金					
	5	Contact material 接触材质		silver alloy 银合金		1		Silvering 镀银					
3	4	Arm nut 固定螺帽		Brass 黄铜		1		nickeling 镀镍					
	3	Oring O型圈		Silica gel 硅胶		1							
	2	Housing 外壳		SUS/Aluminum alloy/Brass 不锈钢/铝合金/黄铜		1							
4	1	Key 按键		SUS/Aluminum alloy/Brass 不锈钢/铝合金/黄铜		1							
	NO 序号	Part name 部件名		Material 材料		QTY 数量		Remark 备注					
A4				 台普 ROCPCU	COMMON TOLERANCE		UNIT	MM	PROJECTED		PRODUCT NAME:		
A3					X.XX	± 0.10	DRAWN BY	SHUHAO	CHECKED BY	COCO	MODEL NO:TP94008P□□□□		
A2					X.X	± 0.15	DATE	2019	APPROVAL B	ALEN	Https: www.rocpcu.tw		
A1					X	± 0.25	ROCPCU TECHNOLOGY CO.,LTD						
REV	DATE	REVISION	DESCRIPTION		ISSUE	ANGULAR							
A		C			D		E		F			G	