


A4				
A3				
A2				
A1				
REV	DATE	REVISION	DESCRIPTION	ISSUE



COMMON TOLERANCE	
X.XX	± 0.10
X.X	± 0.15
X	± 0.25
ANGULAR	—

UNIT	MM	PROJECTED	
DRAWN BY	SHUHAO	CHECKED BY	COCO
DATE	2019	APPROVAL	B ALEN
<b>ROCPCU TECHNOLOGY CO., LTD</b>			
Copies are issued in strict confidence and shall not be reproduced or copied, or used as the basic of manufacture or sale of apparatus without permission			

PRODUCT NAME:	
MODEL NO:	TP92228P□□
Https:	www.rocpcu.tw

	A	B	C	D	E	F	G				
1	<p style="text-align: center;">TP92228P <input type="checkbox"/> <input type="checkbox"/></p> <p><b>Operation method</b>      <b>Material</b></p> <p>1:Self-locking 2:Self-compound</p> <p>A: Aluminum alloy S: Stainless steel B: Brass</p>							1			
2								2			
3	<p><b>性能参数</b></p> <p>1. Rated current:0.1A/DC36V 额定电流:0.1A/DC36V</p> <p>2. Insulation resistance:≥50MΩ 绝缘电阻 :≥50MΩ</p> <p>3. Contact resistance:≤50mΩ 接触电阻 :≤50mΩ</p> <p>4. Pressing stroke:0.50mm ± 0.10 按压行程:0.50mm ± 0.10</p> <p>5. Contact stroke:0.50mm±0.10 接触行程 :0.50mm±0.10</p> <p>6. welding temperature: 320 °C± 20 °C 焊接温度: 320 °C± 20 °C</p> <p>7. Welding duration: Less than 3 seconds in duration 焊接时长: Less than 3 seconds in duration</p> <p>8. Nut assembly torque:5-14N</p> <p style="text-align: right;">螺帽装配力矩:5-14N</p> <p>9. Protection level:IP67 防护等级:IP67</p> <p>10. Explosion prevention level: IK08 防暴等级: IK08</p> <p>11. Working environment temperature: -20 °C~+55 °C 工作环境温度: -20 °C~+55 °C</p> <p>12. Compression torque: ≤ 3N 按压扭力: ≤3N</p> <p>13. Electrical life: 200000 cycles 电气寿命: 200000 cycles</p> <p>14. mechanical: 1000000cycles 机械寿命: 1000000cycles</p> <p>15. NO reverse thrust foot torque: ≤30N NO反推脚扭力: ≤30N</p>							3			
4								4			
5	A4				UNIT	MM	PROJECTED		PRODUCT NAME:		
	A3				DRAWN BY	SHUHAO	CHECKED BY	COCO	MODEL NO: TP92228P <input type="checkbox"/> <input type="checkbox"/>		
	A2				DATE	2019	APPROVAL B	ALEN	Https: www.rocpcu.tw		
	A1				<b>ROCPCU TECHNOLOGY CO.,LTD</b>						
	REV	DATE	REVISION	DESCRIPTION	ISSUE	Copies are issued in strict confidence and shall not be reproduced or copied,or used as the basic of manufacture or sale of apparatus without permission					
		A		B		C		D	E	F	G





COMMON TOLERANCE

X.XX	± 0.10
X.X	± 0.15
X	± 0.25

ANGULAR

NO 序号	Part name 部件名	Material 材料	QTY 数量	Remark 备注
1	Key 按键	SUS/Aluminum alloy/Brass 不锈钢/铝合金/黄铜	1	
2	Housing 外壳	SUS/Aluminum alloy/Brass 不锈钢/铝合金/黄铜	1	
3	Oring O型圈	Silica gel 硅胶	1	
4	Arm nut 固定螺帽	Brass 黄铜	1	nickeling 镀镍
5	Base 基座	PBT	1	
6	Pin 引脚	Brass 黄铜	1	

材质参数

A4				 <b>台普</b> <b>ROCPCU</b>	COMMON TOLERANCE		UNIT	MM	PROJECTED		PRODUCT NAME:
A3					X.XX	± 0.10	DRAWN BY	SHUHAO	CHECKED BY	COCO	MODEL NO: TP92228P□□
A2					X.X	± 0.15	DATE	2019	APPROVAL B	ALEN	Https: www.rocpcu.tw
A1					X	± 0.25	<b>ROCPCU TECHNOLOGY CO.,LTD</b>				
REV	DATE	REVISION	DESCRIPTION		ISSUE	ANGULAR					