





NOTES:
 1. Rating: 100mA 30V DC
 1. 额定值: 100mA 30V DC
 2. Contact Resistance: ≤100mΩ Max
 2. 接触电阻: ≤100mΩ
 3. Operating Force: 200±50gf
 3. 操作力: 200±50gf
 4. Travel: 2.2±0.15mm
 4. 行程: 2.2±0.15mm
 5. Insulation Resistance: ≥100MΩ
 5. 绝缘电阻: ≥100MΩ
 6. Dielectric strength: AC250V 50Hz 1Min
 6. 抗电强度: AC250V 50Hz 1Min
 7. Life: 10,000 times
 7. 寿命: 10,000 次
 8. Operating Temperature: -40°C ~85°C
 8. 使用温度: -40°C ~85°C




常态: 1与3导通, 2与5导通, 4与6导通
 按下: 1与3断开, 2.5.4.6导通

BTSA-□-P-7

Operation
 L : self-locking
 N : lock-free



CIRCUIT DIAGRAM



7	Bearded needle 钩针	SUS	1	本色
6	Spring 弹簧	SUS	1	本色
5	Reed 簧片	Composite silver	2	本色
4	loam cake 上盖	PPA	1	Black 黑色
3	Press handle 按柄	PA6T	1	Beige 米黄色
2	Terminal 端子	Brass	6	本色
1	Pedestal 底座	PPA	1	Black 黑色
NO 序号	Part name 部件名	Material 材料	QTY 数量	Remark 备注

A4				
A3				
A2				
A1				
REV	DATE	REVISION	DESCRIPTION	ISSUE



COMMON TOLERANCE	
X.XX	± 0.10
X.X	± 0.15
X	± 0.25
ANGULAR	—

UNIT	MM	PROJECTED	PRODUCT NAME: BTSA-□-P-7
DRAWN BY	SHUHAO	CHECKED BY	COCO
DATE	2019	APPROVAL	B ALEN
ROCPCU TECHNOLOGY CO.,LTD			
Copies are issued in strict confidence and shall not be reproduced or copied, or used as the basic of manufacture or sale of apparatus without permission			

PRODUCT NAME: BTSA-□-P-7

MODEL NO:

Https: www.rocpcu.tw

ROCPCU TECHNOLOGY CO.,LTD

Copies are issued in strict confidence and shall not be reproduced or copied, or used as the basic of manufacture or sale of apparatus without permission