



A4					 台普 ROCPCU	COMMON TOLERANCE		UNIT	MM	PROJECTED		PRODUCT NAME:
A3				DRAWN BY				FUYUAN	CHECKED BY	COCO	MODEL NO: TP91001P□□□	
A2				DATE		2019	APPROVAL B	ALEN	Https: www.rocpcu.tw			
A1				ROCPCU TECHNOLOGY CO.,LTD								
REV	DATE	REVISION	DESCRIPTION	ISSUE		Copies are issued in strict confidence and shall not be reproduced or copied, or used as the basic of manufacture or sale of apparatus without permission						

TP91001P□□□

LED voltage

- 3: 3V
- 6: 6V
- 12: 12V
- 24: 24V
- 36: 36V
- 48: 48V
- 60: 60V
- 110: 110V
- 220: 220V

Material



- A: Aluminum alloy
- S: Stainless steel
- B: Brass

LED Color

- R: Red
- Y: Yellow
- G: Green
- B: Blue
- W: White
- O: Orange



性能参数

1. Insulation resistance: $\geq 1000M\Omega$
绝缘电阻: $\geq 1000M\Omega$
2. Contact stroke: $1.50mm \pm 0.10$
接触行程: $1.50mm \pm 0.10$
3. welding temperature: $320\text{ }^{\circ}\text{C} \pm 20\text{ }^{\circ}\text{C}$
焊接温度: $320\text{ }^{\circ}\text{C} \pm 20\text{ }^{\circ}\text{C}$
4. Welding duration: Less than 3 seconds in duration
焊接时长: Less than 3 seconds in duration
5. Nut assembly torque: 5-14N
螺帽装配力矩: 5-14N
6. Protection level: IP65
防护等级: IP65
7. Explosion prevention level: IK08
防暴等级: IK08
8. Working environment temperature: $-20\text{ }^{\circ}\text{C} \sim +55\text{ }^{\circ}\text{C}$
工作环境温度: $-20\text{ }^{\circ}\text{C} \sim +55\text{ }^{\circ}\text{C}$
9. LED lamp power consumption: 20m以下
LED灯功耗: 20m以下
10. LED lamp lifespan: 40000h
LED寿命: 40000h

A4				 台普 ROCPCU	COMMON TOLERANCE		UNIT	MM	PROJECTED		PRODUCT NAME:	
A3					X.XX	± 0.10	DRAWN BY	FUYUAN	CHECKED BY	COCO	MODEL NO: TP91001P□□□	
A2					X.X	± 0.15	DATE	2019	APPROVAL B	ALEN	Https: www.rocpcu.tw	
A1					X	± 0.25	ROCPCU TECHNOLOGY CO.,LTD					
REV	DATE	REVISION	DESCRIPTION		ISSUE	ANGULAR						<small>Copies are issued in strict confidence and shall not be reproduced or copied, or used as the basic of manufacture or sale of apparatus without permission</small>
	A		B		C		D		E		F	G

NO 序号	Part name 部件名	Material 材料	QTY 数量	Remark 备注
1	luminous zone 发光区	PC 塑料	1	
2	Housing 外壳	SUS/Aluminum alloy/Brass 不锈钢/铝合金/黄铜	1	
3	Oring O型圈	Silica gel 硅胶	1	
4	Arm nut 固定螺帽	Brass 黄铜	1	nickeling 镀镍
5	Base 基座	PBT	1	
6	LEDpin LED脚	Brass 黄铜	1	Silvering 镀银
7				
8				
9				
10				

材质参数

A4				 ROCPCU	COMMON TOLERANCE	UNIT	MM	PROJECTED		PRODUCT NAME:	
A3					X.XX	? 0.10	DRAWN BY	FUYUAN	CHECKED BY	COCO	MODEL NO: TP91001P <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>
A2					X.X	? 0.15	DATE	2019	APPROVAL B	ALEN	Https: www.rocpcu.tw
A1					X	? 0.25	ROCPCU TECHNOLOGY CO., LTD				
REV	DATE	REVISION	DESCRIPTION		ISSUE	ANGULAR					