



常态: 1-3导通 4-6导通
Normal: 1-3 on 4-6 on
按下: 2-3导通 4-5导通
Press: 2-3 on 4-5 on

Technical parameter
技术参数
1. Rated current: 100mA 30V DC
1. 额定电流: 100mA 30V DC
2. Contact resistance: ≤ 10 Ω
2. 接触电阻: ≤ 10 Ω
3. Operating force: 260gf ± 50gf
3. 操作力: 260gf ± 50gf

4. Maximum stroke: 3.0 ± 0.2mm
4. 最大行程: 3.0 ± 0.2mm
5. Insulation resistance: ≥ 100M Ω
5. 绝缘电阻: ≥ 100M Ω
6. Electric strength: AC250V 50Hz 1min
6. 抗电强度: AC250V 50Hz 1min
7. Service life: 10000 times
7. 寿命: 10000次

BTSA-□-S-18

Operation
L : self-locking
N : lock-free

7	crochet hook 钩针	SUS 不锈钢丝	1	Natural color 本色
6	Spring 弹簧	SUS 不锈钢丝	1	Natural color 本色
5	reed 簧片	Composite silver 复合银	2	Natural color 本色
4	Upper cover 上盖	PPA	1	black 黑色
3	handle 按柄	PPA	1	black 黑色
2	terminal 端子	Brass 黄铜	6	Natural color/silver 本色/镀银
1	Pedestal 基座	PPA	1	black 黑色
ITEM	Name	Materials	NUM	COLOR

A4				
A3				
A2				
A1				
REV	DATE	REVISION	DESCRIPTION	ISSUE



COMMON TOLERANCE	
X.XX	± 0.10
X.X	± 0.15
X	± 0.25
ANGULAR	—

UNIT	MM	PROJECTED	
DRAWN BY	SHUHAO	CHECKED BY	COCO
DATE	2019	APPROVAL B	ALEN

PRODUCT NAME: BTSA-□-S-18	
MODEL NO:	
Https: www.rocpcu.tw	
ROCPCU TECHNOLOGY CO.,LTD	
Copies are issued in strict confidence and shall not be reproduced or copied, or used as the basic of manufacture or sale of apparatus without permission	