






A4					 台普 ROCPCU	COMMON TOLERANCE X.XX ± 0.10 X.X ± 0.15 X ± 0.25 ANGULAR —	UNIT	MM	PROJECTED		PRODUCT NAME:
A3				DRAWN BY			SHUHAO	CHECKED BY	COCO	MODEL NO: TP91222P <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	
A2				DATE			2019	APPROVAL B	ALEN	Https: www.rocpcu.tw	
A1				ROCPCU TECHNOLOGY CO., LTD							
REV	DATE	REVISION	DESCRIPTION	ISSUE			Copies are issued in strict confidence and shall not be reproduced or copied, or used as the basic of manufacture or sale of apparatus without permission				

	A	B	C	D	E	F	G					
1	<div style="display: flex; justify-content: space-around; align-items: center;"> <div style="text-align: center;"> <p>TP91222P</p> <p>Operation method</p> <p>2: Self-compound</p> <p>LED voltage</p> <p>3: 3V 6: 6V 12: 12V 24: 24V 36: 36V 48: 48V</p> </div> <div style="text-align: center;"> <p>Material</p> <p>S: Stainless steel</p> <p>LED Color</p> <p>R: Red Y: Yellow G: Green B: Blue W: White O: Orange</p> </div> </div>											
2												
3	<p>性能参数</p> <ol style="list-style-type: none"> Heating current: Ui: AC220V, Ith: 50mA 发热电流: Ui: AC220V, Ith: 50mA Rated current: 0.10A/DC36V 额定电流: 0.10A/DC36V Power-frequency withstand voltage: 2000V/1min 工频耐压: 2000V/1min Insulation resistance: ≥50MΩ 绝缘电阻: ≥50MΩ Contact resistance: ≤50mΩ 接触电阻: ≤50mΩ Pressing stroke: 0.50mm ± 0.10 按压行程: 0.50mm ± 0.10 Contact stroke: 0.50mm ± 0.10 接触行程: 0.50mm ± 0.10 welding temperature: 320 °C ± 20 °C 焊接温度: 320 °C ± 20 °C Welding duration: Less than 3 seconds in duration 焊接时长: Less than 3 seconds in duration Nut assembly torque: 5-14N 			<ol style="list-style-type: none"> 螺帽装配力矩: 5-14N Protection level: IP67 防护等级: IP67 Explosion prevention level: IK08 防暴等级: IK08 Working environment temperature: -20 °C ~ +55 °C 工作环境温度: -20 °C ~ +55 °C Compression torque: ≤ 3N 按压扭力: ≤ 3N Electrical life: 200000 cycles 电气寿命: 200000 cycles mechanical: 1000000 cycles 机械寿命: 1000000 cycles NO reverse thrust foot torque: ≤ 30N NO反推脚扭力: ≤ 30N LED lamp power consumption: 20m以下 LED灯功耗: 20m以下 LED lamp lifespan: 40000h LED寿命: 40000h 								
4												
5	A4	A3	A2	A1	REV	DATE	REVISION DESCRIPTION ISSUE					
 <p>台普 ROCPCU</p>				COMMON TOLERANCE		UNIT	MM	PROJECTED	⊕	PRODUCT NAME:		
				X.XX	± 0.10	DRAWN BY	SHUHAO	CHECKED BY	COCO	MODEL NO: TP91222P□□□□		
				X.X	± 0.15	DATE	2019	APPROVAL B	ALEN	Https: www.rocpcu.tw		
				X	± 0.25	ROCPCU TECHNOLOGY CO., LTD						
				ANGULAR	Copies are issued in strict confidence and shall not be reproduced or copied, or used as the basic of manufacture or sale of apparatus without permission							
	A	B	C	D	E	F	G					

材质参数

9	luminous zone 发光区	PC 塑料	1		
8	LEDpin LED脚	Brass 黄铜	1	Silvering 镀银	
7	Pin 引脚	Brass 黄铜	1	gold-plating 镀金	
6	Contact material 接触材质	silver alloy 银合金	1	Silvering 镀银	
5	Base 基座	PBT	1		
4	Arm nut 固定螺帽	Brass 黄铜	1	nickeling 镀镍	
3	Oring O型圈	Silica gel 硅胶	1		
2	Housing 外壳	SUS 不锈钢	1		
1	Key 按键	SUS 不锈钢	1		
NO 序号	Part name 部件名	Material 材料	QTY 数量	Remark 备注	

A4				 台普 ROCPCU	COMMON TOLERANCE		UNIT	MM	PROJECTED		PRODUCT NAME:
A3					X.XX	± 0.10	DRAWN BY	SHUHAO	CHECKED BY	COCO	MODEL NO:TP91222P□□□□
A2					X.X	± 0.15	DATE	2019	APPROVAL B	ALEN	Https: www.rocpcu.tw
A1					X	± 0.25	ROCPCU TECHNOLOGY CO.,LTD				
REV	DATE	REVISION	DESCRIPTION		ISSUE	ANGULAR	—	Copies are issued in strict confidence and shall not be reproduced or copied, or used as the basic of manufacture or sale of apparatus without permission			