



- NOTES:**
- 1. Rating: 12VDC 50mA
 - 2. 额定值: 12VDC 50mA
 - 3. Contact Resistance: ≤100mΩ Max
 - 4. 接触电阻: ≤100mΩ
 - 5. Operating Force: 260±50gf
 - 6. Life: 100,000 times
 - 7. Travel: 0.25±0.1mm
 - 8. Operating Temperature: -20 to +70°C
 - 9. 操作力: 260±50gf
 - 10. 寿命: 100,000 times
 - 11. 行程: 0.25 + 0.1mm
 - 12. 使用温度: -20 to +70°C

TPB01-142L LED COLOR

LED COLOR	
1	Red
2	Yellow
3	Green
4	Blue
5	White

8	Transparent cover 透明盖	PC	1	
7	loose coat 外套	PC	1	
6	Key cap 按键帽	ABS	1	
5	LED		1	Blue 蓝色
4	Button 按钮	PA66	1	
3	Shrapnel 弹片	SUS	1	
2	Pedestal 基座	PA66	1	
1	Terminal 端子	Brass	4	Ag plating 镀银
NO 序号	Part name 部件名	Material 材料	QTY 数量	Remark 备注

A4					COMMON TOLERANCE X.XX ± 0.10 X.X ± 0.15 X ± 0.25 ANGULAR —	UNIT	MM	PROJECTED		PRODUCT NAME: TPB01-142L <input type="checkbox"/>		
A3						DRAWN BY	SHUHAO	CHECKED BY	COCO	MODEL NO:		
A2						DATE	2019	APPROVAL B	ALEN	Https:	www.rocpcu.tw	
A1						ROCPCU TECHNOLOGY CO., LTD						
REV	DATE	REVISION	DESCRIPTION			ISSUE	Copies are issued in strict confidence and shall not be reproduced or copied, or used as the basic of manufacture or sale of apparatus without permission					
	A		B			D	E	F		G		