



NOTES:

- 1. Rating: 12VDC 50mA
- 2. Dielectric Strength: 100V AC
- 3. Contact Resistance: ≤100mΩ Max
- 4. Insulation Resistance: ≥100MΩ
- 5. Operating Force: 200±100gf
- 6. Life: 10,000 times
- 7. Operate temperature: -10°C~60°C
- 8. Material Properties: SGS

Height	
20	2.0MM
30	3.0MM
40	4.0MM

TP6101203 Height

NO 序号	Part name 部件名	Material 材料	QTY 数量	Remark 备注
4	Cover 盖子	SUS	1	Silvery white 银白色
3	Contact spring 接触簧片	Bronze	2	Silvery white 银白色
2	Key 按键	Nylon	1	Black 黑色
1	Base 底座	PPA-Brass	4	Ag plating-Black 镀银-黑色

A4				
A3				
A2				
A1				
REV	DATE	REVISION	DESCRIPTION	ISSUE



COMMON TOLERANCE	
X.XX	± 0.10
X.X	± 0.15
X	± 0.25
ANGULAR	—

UNIT	MM	PROJECTED		PRODUCT NAME: TP6101203
DRAWN BY	SHUHAO	CHECKED BY	COCO	MODEL NO:
DATE	2019	APPROVAL B	ALEN	Https: www.rocpcu.tw
ROCPCU TECHNOLOGY CO.,LTD				
Copies are issued in strict confidence and shall not be reproduced or copied, or used as the basic of manufacture or sale of apparatus without permission				