






| | | | | | | | | | | | |
|-----|------|----------|-------------|---|--|-------|---|-----------|---|---------------|------------------------|
| A4 | | | |  台普 ROCPCU | COMMON TOLERANCE X.XX ± 0.10 X.X ± 0.15 X ± 0.25 ANGULAR — | UNIT | MM | PROJECTED |  | PRODUCT NAME: | |
| A3 | | | | | | | DRAWN BY | SHUHAO | CHECKED BY | COCO | MODEL NO: TP92212G□□□□ |
| A2 | | | | | | | DATE | 2019 | APPROVAL B | ALEN | Https: www.rocpcu.tw |
| A1 | | | | | | | ROCPCU TECHNOLOGY CO.,LTD | | | | |
| REV | DATE | REVISION | DESCRIPTION | | | ISSUE | Copies are issued in strict confidence and shall not be reproduced or copied, or used as the basic of manufacture or sale of apparatus without permission | | | | |

| | | | | | | | | | | | |
|---|--|------|----------|---|---|--------|------------|---|---|-------|--|
| | A | B | C | D | E | F | G | | | | |
| 1 | <p>TP92212G <input type="checkbox"/><input type="checkbox"/><input type="checkbox"/><input type="checkbox"/></p> <p>Operation method 1:Self-locking 2:Self-compound</p> <p>LED voltage 3: 3V 6: 6V 12: 12V 24: 24V 36: 36V 48: 48V 60: 60V 110: 110V 220: 220V</p> <p>Material A: Aluminum alloy S: Stainless steel B: Brass</p> <p>LED Color R:Red Y:Yellow G:Green B:Blue W:White O:Orange</p> | | | <p>连接形式</p> <p>1. Welding temperature of wire: 320 ± 20 °C 线材焊接温度: 320±20°C Wire welding duration: less than 3 seconds 线材焊接时长: 时长3秒以下</p> <p>2. Can be used with dedicated connectors: 可配专用接插件使用:</p> <p>2.1 Switch function wire: green (C) blue wire (NO) yellow wire (NC) 开关功能线材: 绿色(C) 蓝线 (NO) 黄线 (NC)</p> <p>2.2 LED functional wire: red wire positive pole black wire negative pole LED without distinguishing positive and negative poles LED功能线材: 红线正极 黑线负极 LED不分正负极</p> | | | | 1 | | | |
| 2 | | | | | | | | 2 | | | |
| 3 | <p>性能参数</p> <p>1. Heating current: Ui: AC250V, Ith: 5A 发热电流: Ui: AC250V, Ith: 5A</p> <p>2. Rated current:3A/DC36V 额定电流:3A/DC36V</p> <p>3. Power-frequency withstand voltage:2000V1min 工频耐压:2000V1min</p> <p>4. Insulation resistance:≥1000MΩ 绝缘电阻 :≥1000MΩ</p> <p>5. Contact resistance:≤50mΩ 接触电阻 :≤50mΩ</p> <p>6. Pressing stroke:3.00mm ± 0.10 按压行程:3.00mm ± 0.10</p> <p>7. Contact stroke:1.50mm±0.10 接触行程 :1.50mm±0.10</p> <p>8. Nut assembly torque:5-14N 螺帽装配力矩:5-14N</p> <p>9. Protection level:IP67 防护等级:IP67</p> | | | <p>10. Explosion prevention level: IK10 防暴等级: IK10</p> <p>11. Working environment temperature: -20 °C~+55 °C 工作环境温度: -20 °C~+55 °C</p> <p>12. Compression torque: ≤6N 按压扭力: ≤6N</p> <p>13. Electrical life: 100000 cycles 电气寿命: 100000 cycles</p> <p>14. mechanical: 500000cycles 机械寿命: 500000cycles</p> <p>15. LED lamp power consumption: 20m以下 LED灯功耗: 20m以下</p> <p>16. LED lamp lifespan: 40000h LED寿命: 40000h</p> <p>17. NO reverse thrust foot torque: ≤30N NO反推脚扭力: ≤30N</p> | | | | 3 | | | |
| 4 | | | | | | | | 4 | | | |
| 5 | A4 | | | | UNIT | MM | PROJECTED |  | PRODUCT NAME: | 5 | |
| | A3 | | | | DRAWN BY | SHUHAO | CHECKED BY | COCO | MODEL NO:TP92212G <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> | | |
| | A2 | | | | DATE | 2019 | APPROVAL B | ALEN | Https: www.rocpu.tw | | |
| | A1 | | | | <p>ROCPU TECHNOLOGY CO.,LTD</p> <p>Copies are issued in strict confidence and shall not be reproduced or copied, or used as the basic of manufacture or sale of apparatus without permission</p> | | | | | | |
| | REV | DATE | REVISION | DESCRIPTION | | | | | | ISSUE | |
| | A | B | C | D | E | F | G | | | | |



| NO 序号 | Part name 部件名 | Material 材料 | QTY 数量 | Remark 备注 |
|----------|--------------------------|--|-----------|--------------------|
| 10 | luminous zone 发光区 | PC 塑胶 | 1 | |
| 9 | LEDpin LED引脚 | Brass 黄铜 | 1 | Silvering 镀银 |
| 8 | Base 底座 | PA46 | 1 | |
| 7 | Pin 引脚 | Brass 黄铜 | 1 | gold-plating 镀金 |
| 6 | Contact material 接触材质 | silver alloy 银合金 | 1 | Silvering 镀银 |
| 5 | LED Base LED基座 | PC 塑胶 | 1 | |
| 4 | Arm nut 固定螺帽 | Brass 黄铜 | 1 | nickeling 镀镍 |
| 3 | Oring O型圈 | Silica gel 硅胶 | 1 | |
| 2 | Housing 外壳 | SUS/Aluminum alloy/Brass 不锈钢/铝合金/黄铜 | 1 | |
| 1 | Key 按键 | SUS/Aluminum alloy/Brass 不锈钢/铝合金/黄铜 | 1 | |

| | | | | | | | | | | | |
|-----|------|----------|-------------|---|------------------|---------|----------------------------------|--------|------------|---|-----------------------|
| A4 | | | |  台普 ROCPCU | COMMON TOLERANCE | | UNIT | MM | PROJECTED |  | PRODUCT NAME: |
| A3 | | | | | X.XX | ± 0.10 | DRAWN BY | SHUHAO | CHECKED BY | COCO | MODEL NO:TP92212G□□□□ |
| A2 | | | | | X.X | ± 0.15 | DATE | 2019 | APPROVAL B | ALEN | Https: www.rocpcu.tw |
| A1 | | | | | X | ± 0.25 | ROCPCU TECHNOLOGY CO.,LTD | | | | |
| REV | DATE | REVISION | DESCRIPTION | | ISSUE | ANGULAR | | | | | |