









A4				 ROCPCU	COMMON TOLERANCE X.XX ± 0.10 X.X ± 0.15 X ± 0.25 ANGULAR —	UNIT	MM	PROJECTED		PRODUCT NAME:	
A3							DRAWN BY	SHUHAO	CHECKED BY	COCO	MODEL NO: TP93001P□□
A2							DATE	2019	APPROVAL B	ALEN	Https: www.rocpcu.tw
A1							ROCPCU TECHNOLOGY CO., LTD				
REV	DATE	REVISION	DESCRIPTION			ISSUE	Copies are issued in strict confidence and shall not be reproduced or copied, or used as the basic of manufacture or sale of apparatus without permission				

		A		B		C		D		E		F		G																																																																																
1																1																																																																														
2		<div style="display: flex; justify-content: space-around; align-items: center;"> <div style="text-align: center;"> <p>TP93001P <input type="checkbox"/> <input type="checkbox"/></p> <p>Operation method</p> <p>1:Self-locking 2:Self-compound</p> </div> <div style="text-align: center;"> <p>Material</p> <p>A: Aluminum alloy S: Stainless steel B: Brass</p> </div> </div>														2																																																																														
3		<div style="display: flex; justify-content: space-between;"> <div style="width: 45%;"> <p>性能参数</p> <ol style="list-style-type: none"> Heating current: Ui: AC250V, Ith: 5A 发热电流: Ui: AC250V, Ith: 5A Rated current:3A/DC36V 额定电流:3A/DC36V Power-frequency withstand voltage:2000V1min 工频耐压:2000V1min Insulation resistance:≥1000MΩ 绝缘电阻 :≥1000MΩ Contact resistance:≤50mΩ 接触电阻 :≤50mΩ Pressing stroke:3.00mm ± 0.10 按压行程:3.00mm ± 0.10 Contact stroke:1.50mm±0.10 接触行程 :1.50mm±0.10 welding temperature: 320 °C± 20 °C 焊接温度: 320 °C± 20 °C Welding duration: Less than 3 seconds in duration </div> <div style="width: 45%;"> <p>连接形式</p> <ol style="list-style-type: none"> Welding temperature of wire: 320 ± 20 °C 线材焊接温度: 320±20°C Wire welding duration: less than 3 seconds 线材焊接时长: 时长3秒以下 Can be used with dedicated connectors: 可配专用接插件使用: 2.1 Switch function wire: green (C) blue wire (NO) yellow wire (NC) 开关功能线材: 绿色(C) 蓝线 (NO) 黄线 (NC) </div> </div>														3																																																																														
4		<div style="display: flex; justify-content: space-between;"> <div style="width: 45%;"> <ol style="list-style-type: none"> Nut assembly torque:5-14N 螺帽装配力矩:5-14N Protection level:IP67 防护等级:IP67 Explosion prevention level: IK10 防暴等级: IK10 Working environment temperature: -20 °C~+55 °C 工作环境温度: -20 °C~+55 °C Compression torque: ≤ 2.5N 按压扭力: ≤2.5N Electrical life: 100000 cycles 电气寿命: 100000 cycles mechanical: 500000cycles 机械寿命: 500000cycles NO reverse thrust foot torque: ≤30N NO反推脚扭力: ≤30N </div> <div style="width: 45%;"> <p>焊接时长: Less than 3 seconds in duration</p> </div> </div>														4																																																																														
5		<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 5%;">A4</td> <td style="width: 5%;"> </td> <td style="width: 5%;"> </td> <td style="width: 5%;"> </td> <td rowspan="5" style="text-align: center; vertical-align: middle;">  ROCPCU </td> <td colspan="2" style="text-align: center;">COMMON TOLERANCE</td> <td style="text-align: center;">UNIT</td> <td style="text-align: center;">MM</td> <td style="text-align: center;">PROJECTED</td> <td style="text-align: center;"></td> <td colspan="5" style="text-align: center;">PRODUCT NAME:</td> </tr> <tr> <td>A3</td> <td> </td> <td> </td> <td> </td> <td style="text-align: center;">X.XX</td> <td style="text-align: center;">± 0.10</td> <td style="text-align: center;">DRAWN BY</td> <td style="text-align: center;">SHUHAO</td> <td style="text-align: center;">CHECKED BY</td> <td style="text-align: center;">COCO</td> <td colspan="5" style="text-align: center;">MODEL NO:TP93001P <input type="checkbox"/> <input type="checkbox"/></td> </tr> <tr> <td>A2</td> <td> </td> <td> </td> <td> </td> <td style="text-align: center;">X.X</td> <td style="text-align: center;">± 0.15</td> <td style="text-align: center;">DATE</td> <td style="text-align: center;">2019</td> <td style="text-align: center;">APPROVAL B</td> <td style="text-align: center;">ALEN</td> <td colspan="5" style="text-align: center;">Https: www.rocpcu.tw</td> </tr> <tr> <td>A1</td> <td> </td> <td> </td> <td> </td> <td style="text-align: center;">X</td> <td style="text-align: center;">± 0.25</td> <td colspan="9" style="text-align: center; font-size: 24px; font-weight: bold;">ROCPCU TECHNOLOGY CO.,LTD</td> </tr> <tr> <td>REV</td> <td>DATE</td> <td>REVISION</td> <td>DESCRIPTION</td> <td>ISSUE</td> <td style="text-align: center;">ANGULAR</td> <td style="text-align: center;">—</td> <td colspan="9" style="text-align: center; font-size: 10px;">Copies are issued in strict confidence and shall not be reproduced or copied, or used as the basic of manufacture or sale of apparatus without permission</td> </tr> </table>														A4				 ROCPCU	COMMON TOLERANCE		UNIT	MM	PROJECTED		PRODUCT NAME:					A3				X.XX	± 0.10	DRAWN BY	SHUHAO	CHECKED BY	COCO	MODEL NO:TP93001P <input type="checkbox"/> <input type="checkbox"/>					A2				X.X	± 0.15	DATE	2019	APPROVAL B	ALEN	Https: www.rocpcu.tw					A1				X	± 0.25	ROCPCU TECHNOLOGY CO.,LTD									REV	DATE	REVISION	DESCRIPTION	ISSUE	ANGULAR	—	Copies are issued in strict confidence and shall not be reproduced or copied, or used as the basic of manufacture or sale of apparatus without permission									5	
A4				 ROCPCU	COMMON TOLERANCE		UNIT	MM	PROJECTED		PRODUCT NAME:																																																																																			
A3					X.XX	± 0.10	DRAWN BY	SHUHAO	CHECKED BY	COCO	MODEL NO:TP93001P <input type="checkbox"/> <input type="checkbox"/>																																																																																			
A2					X.X	± 0.15	DATE	2019	APPROVAL B	ALEN	Https: www.rocpcu.tw																																																																																			
A1					X	± 0.25	ROCPCU TECHNOLOGY CO.,LTD																																																																																							
REV	DATE	REVISION	DESCRIPTION		ISSUE	ANGULAR	—	Copies are issued in strict confidence and shall not be reproduced or copied, or used as the basic of manufacture or sale of apparatus without permission																																																																																						
		A		B		C		D		E		F		G																																																																																

