




PCB LAND DIMENSION
PCB电路板焊盘尺寸



CIRCUIT DIAGRAM
电路图

SPECIFICATION

规范

Rating: 50mA.12V DC

额定值: 50mA.12V DC

Insulation resistance: 100MΩ min.100V DC

绝缘电阻: 100MΩmin.100V DC

Dielectric strength: 250V AC for 1 min

介电强度: 250V AC 1分钟

Contact resistance:100mΩ max

Travel: 0.25±0.1mm

行程: 0.25±0.1mm

Lifetime:600000 times

寿命: 600000 times

Operating temperature rang:-30℃to + 85℃

工作温度范围: -30℃to + 85℃

TP1072

Height

Actuation Force

10 : 100gf

16 : 160gf

26 : 260gf

36 : 360gf

Height	
43	4.3MM
45	4.5MM
50	5.0MM
55	5.5MM
60	6.0MM
65	6.5MM
70	7.0MM
75	7.5MM
80	8.0MM
85	8.5MM
90	9.0MM
95	9.5MM
100	10.0MM
105	10.5MM
110	11.0MM
115	11.5MM
120	12.0MM
125	12.5MM
130	13.0MM

5	Terminal 端子	Brass 黄铜	4	Ag plating 镀银
4	Base 底座	PA6T	1	Black 黑色
3	Contact 弹片	SUS	1	Ag plating 镀银
2	Stem 按钮	PA6T	1	Black 黑色
1	Cover 盖板	Brass 黄铜	1	
NO 序号	Part name 部件名	Material 材料	QTY 数量	Remark 备注

A4				
A3				
A2				
A1				
REV	DATE	REVISION	DESCRIPTION	ISSUE



COMMON TOLERANCE

X.XX	± 0.10
X.X	± 0.15
X	± 0.25

ANGULAR

UNIT	MM	PROJECTED		PRODUCT NAME: TP1072 <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>
DRAWN BY	SHUHAO	CHECKED BY	COCO	MODEL NO:
DATE	2019	APPROVAL B	ALEN	Https: www.rocpcu.tw
ROCPCU TECHNOLOGY CO.,LTD				
Copies are issued in strict confidence and shall not be reproduced or copied, or used as the basic of manufacture or sale of apparatus without permission				