



A4				 台普 ROCPCU	COMMON TOLERANCE X.XX ± 0.10 X.X ± 0.15 X ± 0.25 ANGULAR —	UNIT	MM	PROJECTED		PRODUCT NAME:	
A3							DRAWN BY	SHUHAO	CHECKED BY	COCO	MODEL NO: TP91932G□□□□
A2							DATE	2019	APPROVAL B	ALEN	Https: www.rocpcu.tw
A1							ROCPCU TECHNOLOGY CO., LTD				
REV	DATE	REVISION	DESCRIPTION			ISSUE	Copies are issued in strict confidence and shall not be reproduced or copied, or used as the basic of manufacture or sale of apparatus without permission				



	A	B	C	D	E	F	G			
1	<p>TP91932G <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/></p> <p>Operation method</p> <p>1:Self-locking 2:Self-compound</p> <p>LED voltage</p> <p>3: 3V 6: 6V 12: 12V 24: 24V 36: 36V 48: 48V 60: 60V 110: 110V 220: 220V</p> <p>Material</p> <p>A: Aluminum alloy S: Stainless steel B: Brass</p> <p>LED Color</p> <p>R:Red Y:Yellow G:Green B:Blue W:White O:Orange</p>			<p>连接形式</p> <ol style="list-style-type: none"> Welding temperature of wire: 320 ± 20 °C 线材焊接温度: 320±20°C Wire welding duration: less than 3 seconds 线材焊接时长: 时长3秒以下 Can be used with dedicated connectors: 可配专用接插件使用: <ol style="list-style-type: none"> Switch function wire: blue wire (NO) 开关功能线材: 蓝线 (NO) LED functional wire: red wire positive pole, black wire negative pole, LED without distinction between positive and negative poles LED功能线材: 红线正极, 黑线负极, LED不分正负极 				1		
2								2		
3	<p>性能参数</p> <ol style="list-style-type: none"> Heating current: Ui: AC250V, Ith: 5A 发热电流: Ui: AC250V, Ith: 5A Rated current:3A/DC36V 额定电流:3A/DC36V Power-frequency withstand voltage:1500V1min 工频耐压:1500V1min Insulation resistance:≥1000MΩ 绝缘电阻 :≥1000MΩ Contact resistance:≤50mΩ 接触电阻 :≤50mΩ Pressing stroke:2.80mm ± 0.10 按压行程:2.80mm ± 0.10 Contact stroke:1.00mm±0.10 接触行程 :1.00mm±0.10 Nut assembly torque:5-14N 螺帽装配力矩:5-14N Protection level:IP67 			<p>防护等级:IP67</p> <ol style="list-style-type: none"> Explosion prevention level: IK10 防暴等级: IK10 Working environment temperature: -20 °C~+55 °C 工作环境温度: -20 °C~+55 °C Compression torque: ≤ 4N 按压扭力: ≤4N Electrical life: 500000 cycles 电气寿命: 500000 cycles mechanical: 500000cycles 机械寿命: 500000cycles NO reverse thrust foot torque: ≤30N NO反推脚扭力: ≤30N LED lamp power consumption: 20m以下 LED灯功耗: 20m以下 LED lamp lifespan: 40000h LED寿命: 40000h 				3		
4								4		
5	A4				UNIT	MM	PROJECTED		PRODUCT NAME:	5
	A3				DRAWN BY	SHUHAO	CHECKED BY	COCO	MODEL NO: TP91932G <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	
	A2				DATE	2019	APPROVAL B	ALEN	Https: www.rocpu.tw	
	A1				ROCPU TECHNOLOGY CO.,LTD					
	REV	DATE	REVISION	DESCRIPTION						ISSUE
		A	B	C	D	E	F	G		



COMMON TOLERANCE	
X.XX	± 0.10
X.X	± 0.15
X	± 0.25
ANGULAR	—

Copies are issued in strict confidence and shall not be reproduced or copied, or used as the basic of manufacture or sale of apparatus without permission

NO 序号	Part name 部件名	Material 材料	QTY 数量	Remark 备注
10	luminous zone 发光区	PC 塑料	1	
9	LEDpin LED脚	Brass 黄铜	1	Silvering 镀银
8	Base 底座	PA46	1	
7	Pin 引脚	Brass 黄铜	1	gold-plating 镀金
6	Contact material 接触材质	silver alloy 银合金	1	Silvering 镀银
5	Base 基座	PA66	1	
4	Arm nut 固定螺帽	Brass 黄铜	1	nickeling 镀镍
3	Oring O型圈	Silica gel 硅胶	1	
2	Housing 外壳	SUS/Aluminum alloy/Brass 不锈钢/铝合金/黄铜	1	
1	Key 按键	SUS/Aluminum alloy/Brass 不锈钢/铝合金/黄铜	1	

A4				 台普 ROCPCU	COMMON TOLERANCE		UNIT	MM	PROJECTED		PRODUCT NAME:
A3					X.XX	± 0.10	DRAWN BY	SHUHAO	CHECKED BY	COCO	MODEL NO: TP91932G□□□□
A2					X.X	± 0.15	DATE	2019	APPROVAL B	ALEN	Https: www.rocpcu.tw
A1					X	± 0.25	ROCPCU TECHNOLOGY CO.,LTD				
REV	DATE	REVISION	DESCRIPTION		ISSUE	ANGULAR					