



NOTES:

1. Rate voltage: 50mA DC12V
1.额定电压: 50mA DC12V
2. Contact resistance: ≤100mΩ
2.接触电阻: ≤100mΩ
3. Travel: 0.20±0.10mm
3.行程: 0.20±0.10mm

4. Insulated resistance: ≥100mΩ
4.绝缘电阻: ≥100mΩ
5. Dielectric strength: ≥250VAC
5.介电强度: ≥250VAC
6. Life: 50000 times
6.寿命: 50000次
7. Working temperature: -20℃~80℃
7.工作温度: -20℃~80℃

Height	
38	3.8MM
43	4.3MM
50	5.0MM

TP1272 □ □ □ □

Height

Actuation Force

16 : 160gf

26 : 260gf

5	Push-button 按钮	PPA	1	Black 黑色
4	Blind flange 盖板	Iron cover plate	1	Copper tin plating 镀铜锡
3	Shrapnel 弹片	SUS	1	Ag plating 镀银
2	Noumenon 本体	PPA	1	Black 黑色
1	Card 卡件	Brass	1	Ag plating 镀银
NO 序号	Part name 部件名	Material 材料	QTY 数量	Remark 备注

A4				
A3				
A2				
A1				
REV	DATE	REVISION	DESCRIPTION	ISSUE



COMMON TOLERANCE

X.XX	± 0.10
X.X	± 0.15
X	± 0.25

ANGULAR

UNIT	MM	PROJECTED		PRODUCT NAME: TP1272 □ □ □ □
DRAWN BY	SHUHAO	CHECKED BY	COCO	MODEL NO:
DATE	2019	APPROVAL B	ALEN	Https: www.rocpcu.tw
ROCPCU TECHNOLOGY CO.,LTD				
Copies are issued in strict confidence and shall not be reproduced or copied, or used as the basic of manufacture or sale of apparatus without permission				