



NOTES:

1. Rate voltage: 50mA DC
1. 额定电压: 50mA DC
2. Contact resistance: ≤100mΩ
2. 接触电阻: ≤100mΩ
3. Travel: 0.20±0.10mm
3. 行程: 0.20±0.10mm

4. Insulated resistance: ≥100MΩ
4. 绝缘电阻: ≥100MΩ
5. Dielectric strength: ≥250VAC
5. 介电强度: ≥250VAC
6. Working temperature: -20°C~80°C
6. 工作温度: -20°C~80°C
7. life: 20000times
7. 寿命: 20000次

TP1242 □ □ □ □

Actuation Force
16 : 160gf
26 : 260gf

Height	
43	4.3MM
46	4.6MM
50	5.0MM
63	6.3MM
73	7.3MM

5	Push-button 按钮	PAA	1	white 白色
4	Blind flange 盖板	Yellow metal	1	Ag plating 镀银
3	Shrapnel 弹片	SUS	1	Ag plating 镀银
2	Noumenon 本体	PPA	1	Black 黑色
1	Card 卡件	Yellow metal	1	Ag plating 镀银
NO 序号	Part name 部件名	Material 材料	QTY 数量	Remark 备注

A4				
A3				
A2				
A1				
REV	DATE	REVISION	DESCRIPTION	ISSUE



COMMON TOLERANCE	
X.XX	± 0.10
X.X	± 0.15
X	± 0.25
ANGULAR	—

UNIT	MM	PROJECTED		PRODUCT NAME: TP1242 □ □ □ □
DRAWN BY	SHUHAO	CHECKED BY	COCO	MODEL NO:
DATE	2019	APPROVAL B	ALEN	Https: www.rocpcu.tw
ROCPCU TECHNOLOGY CO., LTD				
Copies are issued in strict confidence and shall not be reproduced or copied, or used as the basic of manufacture or sale of apparatus without permission				