



Circuit Diagram



**Main Specifications**  
 主要技术指标  
 Climate grade: -30°C~70°C  
 工作温度: -30°C~70°C  
 Rated values: 0.5A/12V  
 额定值: 0.5A/12V  
 Contact resistance: ≤500mΩ  
 接触电阻: ≤500mΩ  
 Dielectric strength: 250V,AC,1Min

耐压: 250V,AC,1Min  
 Insulation resistance: ≥100MΩ  
 绝缘电阻: ≥100MΩ  
 Travel: 0.20±0.05mm  
 行程: 0.20±0.05mm  
 Life: 50,000 times  
 寿命: 50,000 times

TP1022

Height  
18:1.8MM

Actuation Force  
16 : 160gf  
26 : 260gf

7	Plastic upper cover 塑胶上盖	PA6T	1	Natural color 本色
6	Yellow membrane 黄膜	Teflon 铁氟龙	1	Yellow 黄色
5	Pin 引脚	Phosphor copper 磷铜	1	Silver 镀银
4	base 塑胶底座	PA6T 尼龙6T	1	Black 黑色
3	Shrapnel 弹片	SUS 不锈钢	2	Silver 单面镀银
2	Plastic key 塑胶按钮	PA6T 尼龙6T	1	Natural color 本色
1	Cover plate 盖板	Brass 黄铜	1	Silver 镀银
ITEM	Name	Materials	NUM	COLOR

A4				
A3				
A2				
A1				
REV	DATE	REVISION	DESCRIPTION	ISSUE



COMMON TOLERANCE	
X.XX	± 0.10
X.X	± 0.15
X	± 0.25
ANGULAR	—

UNIT	MM	PROJECTED	PRODUCT NAME:
DRAWN BY	SHUHAO	CHECKED BY	MODEL NO: TP1022 <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>
DATE	2019	APPROVAL B	Https: www.rocpu.tw
<b>ROCPU TECHNOLOGY CO.,LTD</b>			
Copies are issued in strict confidence and shall not be reproduced or copied, or used as the basic of manufacture or sale of apparatus without permission			