












A4				 台普 ROCPCU	COMMON TOLERANCE X.XX ± 0.10 X.X ± 0.15 X ± 0.25 ANGULAR —	UNIT	MM	PROJECTED		PRODUCT NAME:	
A3			DRAWN BY			SHUHAO	CHECKED BY	COCO	MODEL NO: TP92216G	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	
A2			DATE			2019	APPROVAL B	ALEN	Https: www.rocpcu.tw		
A1			ROCPCU TECHNOLOGY CO.,LTD								
REV	DATE	REVISION	DESCRIPTION			ISSUE	Copies are issued in strict confidence and shall not be reproduced or copied, or used as the basic of manufacture or sale of apparatus without permission				

	A	B	C	D	E	F	G			
1	<p>TP92216G    </p> <p>Operation method 1:Self-locking 2:Self-compound</p> <p>LED voltage 3: 3V 6: 6V 12: 12V 24: 24V 36: 36V 48: 48V 60: 60V 110: 110V 220: 220V</p> <p>Material A: Aluminum alloy S: Stainless steel B: Brass</p> <p>LED Color R: Red Y: Yellow G: Green B: Blue W: White O: Orange</p>			<p>连接形式</p> <ol style="list-style-type: none"> Welding temperature of wire: 320 ± 20 °C 线材焊接温度: 320±20°C Wire welding duration: less than 3 seconds 线材焊接时长: 时长3秒以下 Can be used with dedicated connectors: 可配专用接插件使用: <ol style="list-style-type: none"> Switch function wire: green (C) blue wire (NO) yellow wire (NC) 开关功能线材: 绿色(C) 蓝线 (NO) 黄线 (NC) LED functional wire: red wire positive pole black wire negative pole LED without distinguishing positive and negative poles LED功能线材: 红线正极 黑线负极 LED不分正负极 				1		
2								2		
3	<p>性能参数</p> <ol style="list-style-type: none"> Heating current: Ui: AC250V, Ith: 5A 发热电流: Ui: AC250V, Ith: 5A Rated current: 3A/DC36V 额定电流: 3A/DC36V Power-frequency withstand voltage: 2000V1min 工频耐压: 2000V1min Insulation resistance: ≥1000MΩ 绝缘电阻 : ≥1000MΩ Contact resistance: ≤50mΩ 接触电阻 : ≤50mΩ Pressing stroke: 3.00mm ± 0.10 按压行程: 3.00mm ± 0.10 Contact stroke: 1.50mm ± 0.10 接触行程 : 1.50mm ± 0.10 Nut assembly torque: 5-14N 螺帽装配力矩: 5-14N Protection level: IP67 防护等级: IP67 			<ol style="list-style-type: none"> Explosion prevention level: IK10 防暴等级: IK10 Working environment temperature: -20 °C ~ +55 °C 工作环境温度: -20 °C ~ +55 °C Compression torque: ≤6N 按压扭力: ≤6N Electrical life: 100000 cycles 电气寿命: 100000 cycles mechanical: 500000 cycles 机械寿命: 500000 cycles LED lamp power consumption: 20m 以下 LED灯功耗: 20m 以下 LED lamp lifespan: 40000h LED寿命: 40000h NO reverse thrust foot torque: ≤30N NO反推脚扭力: ≤30N 				3		
4								4		
5	A4				UNIT	MM	PROJECTED		PRODUCT NAME:	
	A3				DRAWN BY	SHUHAO	CHECKED BY	COCO	MODEL NO: TP92216G    	
	A2				DATE	2019	APPROVAL B	ALEN	Https: www.rocpcu.tw	
	A1				ROCPU TECHNOLOGY CO., LTD					
	REV	DATE	REVISION	DESCRIPTION						ISSUE
		A	B	C	D	E	F	G		





COMMON TOLERANCE

X.XX	± 0.10
X.X	± 0.15
X	± 0.25

ANGULAR

Copies are issued in strict confidence and shall not be reproduced or copied, or used as the basic of manufacture or sale of apparatus without permission

A		B		C		D		E		F		G	
材质参数													
1	10	luminous zone 发光区		PC 塑胶		1							
	9	LEDpin LED引脚		Brass 黄铜		1		Silvering 镀银					
2	8	Base 底座		PA46		1							
	7	Pin 引脚		Brass 黄铜		1		gold-plating 镀金					
	6	Contact material 接触材质		silver alloy 银合金		1		Silvering 镀银					
3	5	LED Base LED基座		PC 塑胶		1							
	4	Arm nut 固定螺帽		Brass 黄铜		1		nickeling 镀镍					
	3	Oring O型圈		Silica gel 硅胶		1							
4	2	Housing 外壳		SUS/Aluminum alloy/Brass 不锈钢/铝合金/黄铜		1							
	1	Key 按键		SUS/Aluminum alloy/Brass 不锈钢/铝合金/黄铜		1							
	NO 序号	Part name 部件名		Material 材料		QTY 数量		Remark 备注					
A4				 台普 ROCPCU	COMMON TOLERANCE		UNIT	MM	PROJECTED		PRODUCT NAME:		
A3					X.XX	± 0.10	DRAWN BY	SHUHAO	CHECKED BY	COCO	MODEL NO:TP92216G□□□□		
A2					X.X	± 0.15	DATE	2019	APPROVAL B	ALEN	Https: www.rocpcu.tw		
A1					X	± 0.25	ROCPCU TECHNOLOGY CO.,LTD						
REV	DATE	REVISION	DESCRIPTION		ISSUE	ANGULAR							
A		C			D		E		F			G	