







A4				 台普 ROCPCU	COMMON TOLERANCE X.XX ± 0.10 X.X ± 0.15 X ± 0.25 ANGULAR —	UNIT	MM	PROJECTED		PRODUCT NAME:	
A3			DRAWN BY			SHUHAO	CHECKED BY	COCO	MODEL NO: TP94001P <input type="checkbox"/> <input type="checkbox"/>		
A2			DATE			2019	APPROVAL B	ALEN	Https: www.rocpcu.tw		
A1			ROCPCU TECHNOLOGY CO., LTD								
REV	DATE	REVISION	DESCRIPTION			ISSUE	Copies are issued in strict confidence and shall not be reproduced or copied, or used as the basic of manufacture or sale of apparatus without permission				

A		B		C		D		E		F		G	
<div style="display: flex; justify-content: space-between;"> <div style="width: 45%;"> <p style="text-align: center;">TP94001P <input type="checkbox"/> <input type="checkbox"/></p> <p>Operation method</p> <p>1:Self-locking 2:Self-compound</p> </div> <div style="width: 45%;"> <p>Material</p> <p>A: Aluminum alloy S: Stainless steel B: Brass</p> </div> </div> <div style="margin-top: 20px;"> <p>性能参数</p> <ol style="list-style-type: none"> Heating current: Ui: AC250V, Ith: 5A 发热电流: Ui: AC250V, Ith: 5A Rated current:3A/DC36V 额定电流:3A/DC36V Power-frequency withstand voltage:2000V/1min 工频耐压:2000V/1min Insulation resistance:≥1000MΩ 绝缘电阻 :≥1000MΩ Contact resistance:≤50mΩ 接触电阻 :≤50mΩ Pressing stroke:2.50mm ± 0.10 按压行程:2.50mm ± 0.10 Contact stroke:1.50mm±0.10 接触行程 :1.50mm±0.10 welding temperature: 320 °C± 20 °C 焊接温度: 320 °C± 20 °C Welding duration: Less than 3 seconds in duration </div> <div style="margin-top: 20px;"> <p>连接形式</p> <ol style="list-style-type: none"> Welding temperature of wire: 320 ± 20 °C 线材焊接温度: 320±20°C Wire welding duration: less than 3 seconds 线材焊接时长: 时长3秒以下 Can be used with dedicated connectors: 可配专用接插件使用: 2.1 Switch function wire: Green Line (C) Blue Line (NO) Yellow Line (NC) 开关功能线材: 绿线 (C) 蓝线 (NO) 黄线 (NC) </div> <div style="margin-top: 20px;"> <p>性能参数</p> <ol style="list-style-type: none"> Heating current: Ui: AC250V, Ith: 5A 发热电流: Ui: AC250V, Ith: 5A Rated current:3A/DC36V 额定电流:3A/DC36V Power-frequency withstand voltage:2000V/1min 工频耐压:2000V/1min Insulation resistance:≥1000MΩ 绝缘电阻 :≥1000MΩ Contact resistance:≤50mΩ 接触电阻 :≤50mΩ Pressing stroke:2.50mm ± 0.10 按压行程:2.50mm ± 0.10 Contact stroke:1.50mm±0.10 接触行程 :1.50mm±0.10 welding temperature: 320 °C± 20 °C 焊接温度: 320 °C± 20 °C Welding duration: Less than 3 seconds in duration </div> <div style="margin-top: 20px;"> <p>性能参数</p> <ol style="list-style-type: none"> Heating current: Ui: AC250V, Ith: 5A 发热电流: Ui: AC250V, Ith: 5A Rated current:3A/DC36V 额定电流:3A/DC36V Power-frequency withstand voltage:2000V/1min 工频耐压:2000V/1min Insulation resistance:≥1000MΩ 绝缘电阻 :≥1000MΩ Contact resistance:≤50mΩ 接触电阻 :≤50mΩ Pressing stroke:2.50mm ± 0.10 按压行程:2.50mm ± 0.10 Contact stroke:1.50mm±0.10 接触行程 :1.50mm±0.10 welding temperature: 320 °C± 20 °C 焊接温度: 320 °C± 20 °C Welding duration: Less than 3 seconds in duration </div>													
A4				 台普 ROCPCU	COMMON TOLERANCE		UNIT	MM	PROJECTED		PRODUCT NAME:		
A3								DRAWN BY	SHUHAO	CHECKED BY	COCO	MODEL NO:TP94001P <input type="checkbox"/> <input type="checkbox"/>	
A2					X.XX	± 0.10	DATE	2019	APPROVAL B	ALEN	Https: www.rocpu.tw		
A1					X.X	± 0.15	ROCPCU TECHNOLOGY CO.,LTD						
REV	DATE	REVISION	DESCRIPTION		ISSUE	X							± 0.25
					ANGULAR	—	Copies are issued in strict confidence and shall not be reproduced or copied, or used as the basis of manufacture or sale of apparatus without permission						
A		B		C		D		E		F		G	

NO 序号	Part name 部件名	Material 材料	QTY 数量	Remark 备注
1	Key 按键	SUS/Aluminum alloy/Brass 不锈钢/铝合金/黄铜	1	
2	Housing 外壳	SUS/Aluminum alloy/Brass 不锈钢/铝合金/黄铜	1	
3	Oring O型圈	Silica gel 硅胶	1	
4	Arm nut 固定螺帽	Brass 黄铜	1	nickeling 镀镍
5	Contact material 接触材质	silver alloy 银合金	1	Silvering 镀银
6	NOPin NO引脚	Brass 黄铜	1	gold-plating 镀金
7	Base 底座	PA46	1	Silvering 镀银
8				
9				

A4				 ROCPCU	COMMON TOLERANCE		UNIT	MM	PROJECTED		PRODUCT NAME:
A3					X.XX	± 0.10	DRAWN BY	SHUHAO	CHECKED BY	COCO	MODEL NO:TP94001P□□□□
A2					X.X	± 0.15	DATE	2019	APPROVAL B	ALEN	Https: www.rocpcu.tw
A1					X	± 0.25	ROCPCU TECHNOLOGY CO.,LTD				
REV	DATE	REVISION	DESCRIPTION		ISSUE	ANGULAR					