



NOTES:

- 1. Rating: 12VDC 50mA
- 1. 额定值: 12VDC 50mA
- 2. Dielectric Strength: 250V AC
- 2. 耐电压: 250V AC
- 3. Contact Resistance: ≤100mΩ Max
- 3. 接触电阻: ≤100mΩ
- 4. Insulation Resistance: ≥100MΩ
- 4. 绝缘电阻: ≥100MΩ

- 5. Life: 100,000 times
- 5. 寿命: 100,000 times
- 6. Travel: 0.20±0.1mm
- 6. 行程: 0.20 + 0.1mm
- 9. Operating Temperature: -20 to +70°C
- 9. 使用温度: -20 to +70°C

TP1142 □ □ □ □

Height

Actuation Force

16 : 160gf

26 : 260gf

35 : 350gf

Height	
43	4.3MM
45	4.5MM
50	5.0MM
55	5.5MM
60	6.0MM
65	6.5MM
70	7.0MM
75	7.5MM
80	8.0MM
85	8.5MM
90	9.0MM
95	9.5MM
100	10.0MM
105	10.5MM
110	11.0MM
115	11.5MM
120	12.0MM
125	12.5MM
130	13.0MM

5	Button 按钮	PA6T	1	Red 红色
4	COVER 盖板	Brass	1	
3	Shrapnel 弹片	SUS	1	Ag plating 镀银
2	Terminal 端子	Brass	4	Ag plating 镀银
1	Pedestal 基座	PA6T	1	Black 黑色
NO 序号	Part name 部件名	Material 材料	QTY 数量	Remark 备注

A4				
A3				
A2				
A1				
REV	DATE	REVISION	DESCRIPTION	ISSUE



COMMON TOLERANCE	
X.XX	± 0.10
X.X	± 0.15
X	± 0.25
ANGULAR	—

UNIT	MM	PROJECTED		PRODUCT NAME: TP1142 □ □ □ □
DRAWN BY	SHUHAO	CHECKED BY	COCO	MODEL NO:
DATE	2019	APPROVAL B	ALEN	Https: www.rocpcu.tw
<b>ROCPCU TECHNOLOGY CO., LTD</b>				
Copies are issued in strict confidence and shall not be reproduced or copied, or used as the basic of manufacture or sale of apparatus without permission				