


PCB WELEING DRAWING



CIRCUIT DIAGRAM

Product specifications

产品规格

1.Current: 50mA 48V DC/AC Max
1uA 20mV DC/AC Min

1.电流: 最大50mA 48V直流/交流
1uA 20mV直流/交流最小值

2.Electrical Life:40,000 times

2.电气寿命: 40000次

3.Contact Resistance:50 mΩ max

3.接触电阻: 最大50 mΩ

4.Insulation Resistance:1,000 MΩ min

4.绝缘电阻: 最小1000MΩ

5.Dielectric Strength:500 V RMS

5.介电强度: 500 V RMS

6.Operating Temperature:-30°C to + 85°C

6.工作温度: -30°C至 + 85°C

7. Operating force:400±50gf

7.操作力: 400±50gf

8.Waterproof grade: IP67

8.防水等级: IP67

9	DASE 底座	PA66	1	
8	Handle 手柄	PA66	1	
7	Upper lid 上盖	PA66	1	
6	TERMINAL 端子	Copper alloy 铜合金	6	gold plated 镀金
5	Contact strip 接触片	Copper alloy 铜合金	1	silver plated 镀银
4	SWITCH SUPPORT 支架	Copper alloy 铜合金	1	tin-lead 镀铅
3	SLIDE BUTTON 防尘垫圈	rubber	1	
2	waterproof cover 防水罩	Silica gel 硅胶	1	
1	Spring 弹簧	SWC-80C	1	
NO 序号	Part name 部件名	Material 材料	QTY 数量	Remark 备注

A4				
A3				
A2				
A1				
REV	DATE	REVISION	DESCRIPTION	ISSUE
	A			B



COMMON TOLERANCE

X.XX	± 0.10
X.X	± 0.15
X	± 0.25

ANGULAR

UNIT	MM	PROJECTED		PRODUCT NAME:
DRAWN BY	FUYUAN	CHECKED BY	COCO	MODEL NO: TP60511023
DATE	2019	APPROVAL B	ALEN	Https: www.rocpu.tw
ROCPCU TECHNOLOGY CO.,LTD				
Copies are issued in strict confidence and shall not be reproduced or copied, or used as the basic of manufacture or sale of apparatus without permission				
D	E	F	G	