






	A	B	C	D	E	F	G																								
1	<p>TP91603P <input type="checkbox"/><input type="checkbox"/><input type="checkbox"/><input type="checkbox"/></p> <p>Operation method 1:Self-locking 2:Self-compound</p> <p>LED voltage 3: 3V 6: 6V 12: 12V 24: 24V 36: 36V 48: 48V 60: 60V 110: 110V 220: 220V</p>		<p>Material A: Aluminum alloy S: Stainless steel B: Brass</p> <p>LED Color R:Red Y:Yellow G:Green B:Blue W:White O:Orange</p>	<p>连接形式</p> <p>1. Welding temperature of wire: 320 ± 20 °C 线材焊接温度: 320±20℃ Wire welding duration: less than 3 seconds 线材焊接时长: 时长3秒以下</p> <p>2. Can be used with dedicated connectors: 可配专用接插件使用:</p> <p>2.1 Switch function wire: green (C) blue wire (NO) yellow wire (NC) 开关功能线材: 绿色(C) 蓝线 (NO) 黄线 (NC)</p> <p>2.2 LED functional wire: red wire positive pole, black wire negative pole, LED without distinction between positive and negative poles LED功能线材: 红线正极, 黑线负极, LED不分正负极</p>				1																							
2																															
3	<p>性能参数</p> <p>1. Heating current: Ui: AC250V, Ith: 5A 发热电流: Ui: AC250V, Ith: 5A</p> <p>2. Rated current:3A/DC36V 额定电流:3A/DC36V</p> <p>3. Power-frequency withstand voltage:2000V1min 工频耐压:2000V1min</p> <p>4. Insulation resistance:≥1000MΩ 绝缘电阻 :≥1000MΩ</p> <p>5. Contact resistance:≤50mΩ 接触电阻 :≤50mΩ</p> <p>6. Pressing stroke:2.80mm ± 0.10 按压行程:2.80mm ± 0.10</p> <p>7. Contact stroke:1.50mm±0.10 接触行程 :1.50mm±0.10</p> <p>8. Nut assembly torque:5-14N 螺帽装配力矩:5-14N</p> <p>9. Protection level:IP67 防护等级:IP67</p>																														
4																															
5	A4																														
	A3																														
	A2																														
	A1																														
	REV	DATE	REVISION DESCRIPTION	ISSUE	<p>COMMON TOLERANCE</p> <table border="1"> <tr> <td>X.XX</td> <td>± 0.10</td> </tr> <tr> <td>X.X</td> <td>± 0.15</td> </tr> <tr> <td>X</td> <td>± 0.25</td> </tr> <tr> <td>ANGULAR</td> <td>—</td> </tr> </table>			X.XX	± 0.10	X.X	± 0.15	X	± 0.25	ANGULAR	—	<table border="1"> <tr> <td>UNIT</td> <td>MM</td> <td>PROJECTED</td> <td></td> <td>PRODUCT NAME:</td> </tr> <tr> <td>DRAWN BY</td> <td>SHUHAO</td> <td>CHECKED BY</td> <td>COCO</td> <td>MODEL NO:TP91603P<input type="checkbox"/><input type="checkbox"/><input type="checkbox"/><input type="checkbox"/></td> </tr> <tr> <td>DATE</td> <td>2019</td> <td>APPROVAL B</td> <td>ALEN</td> <td>Https: www.rocpu.tw</td> </tr> </table> <p>ROCPU TECHNOLOGY CO.,LTD</p> <p>Copies are issued in strict confidence and shall not be reproduced or copied,or used as the basic of manufacture or sale of apparatus without permission</p>	UNIT	MM	PROJECTED		PRODUCT NAME:	DRAWN BY	SHUHAO	CHECKED BY	COCO	MODEL NO:TP91603P <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	DATE	2019	APPROVAL B	ALEN	Https: www.rocpu.tw
X.XX	± 0.10																														
X.X	± 0.15																														
X	± 0.25																														
ANGULAR	—																														
UNIT	MM	PROJECTED		PRODUCT NAME:																											
DRAWN BY	SHUHAO	CHECKED BY	COCO	MODEL NO:TP91603P <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>																											
DATE	2019	APPROVAL B	ALEN	Https: www.rocpu.tw																											
	A	B	C	D	E	F	G																								

NO 序号	Part name 部件名	Material 材料	QTY 数量	Remark 备注
10	luminous zone 发光区	PC 塑料	1	
9	LEDpin LED脚	Brass 黄铜	1	Silvering 镀银
8	Base 底座	PA46	1	
7	Pin 引脚	Brass 黄铜	1	gold-plating 镀金
6	Contact material 接触材质	silver alloy 银合金	1	Silvering 镀银
5	LED Base LED基座	PBT	1	
4	Arm nut 固定螺帽	Brass 黄铜	1	nickeling 镀镍
3	Oring O型圈	Silica gel 硅胶	1	
2	Housing 外壳	Aluminum alloy/SUS/Brass 铝合金/不锈钢/黄铜	1	
1	Key 按键	Aluminum alloy/SUS/Brass 铝合金/不锈钢/黄铜	1	

A4				 台普 ROCPCU	COMMON TOLERANCE		UNIT	MM	PROJECTED		PRODUCT NAME:
A3					X.XX	± 0.10	DRAWN BY	SHUHAO	CHECKED BY	COCO	MODEL NO: TP91603P□□□□
A2					X.X	± 0.15	DATE	2019	APPROVAL B	ALEN	Https: www.rocpcu.tw
A1					X	± 0.25	ROCPCU TECHNOLOGY CO.,LTD				
REV	DATE	REVISION	DESCRIPTION		ISSUE	ANGULAR					