







A4				 台普 ROCPCU	COMMON TOLERANCE X.XX ± 0.10 X.X ± 0.15 X ± 0.25 ANGULAR —	UNIT	MM	PROJECTED		PRODUCT NAME:	
A3						DRAWN BY	FUYUAN	CHECKED BY	COCO	MODEL NO: TP91201P□□	
A2						DATE	2019	APPROVAL B	ALEN	Https: www.rocpcu.tw	
A1						ROCPCU TECHNOLOGY CO.,LTD					
REV	DATE	REVISION	DESCRIPTION			ISSUE	Copies are issued in strict confidence and shall not be reproduced or copied, or used as the basic of manufacture or sale of apparatus without permission				

A		B		C		D		E		F		G	
<p style="text-align: center;">TP91201P <input type="checkbox"/> <input type="checkbox"/></p> <p>Operation method <input type="checkbox"/> <input type="checkbox"/> Material</p> <p>1: Self-locking 2: Self-compound</p> <p>A: Aluminum alloy S: Stainless steel B: Brass</p> <p>性能参数</p> <ol style="list-style-type: none"> Heating current: Ui: AC250V, Ith: 3A 发热电流: Ui: AC250V, Ith: 3A Rated current: 2A/DC36V 额定电流: 2A/DC36V Insulation resistance: $\geq 1000M\Omega$ 绝缘电阻: $\geq 1000M\Omega$ Contact resistance: $\leq 50m\Omega$ 接触电阻: $\leq 50m\Omega$ Pressing stroke: $2.30mm \pm 0.10$ 按压行程: $2.30mm \pm 0.10$ Contact stroke: $1.00mm \pm 0.10$ 接触行程: $1.00mm \pm 0.10$ welding temperature: $320^\circ C \pm 20^\circ C$ 焊接温度: $320^\circ C \pm 20^\circ C$ Welding duration: Less than 3 seconds in duration 焊接时长: Less than 3 seconds in duration Nut assembly torque: 5-14N 螺帽装配力矩: 5-14N Protection level: IP65 防护等级: IP65 Explosion prevention level: IK08 防暴等级: IK08 Working environment temperature: $-20^\circ C \sim +55^\circ C$ 工作环境温度: $-20^\circ C \sim +55^\circ C$ Compression torque: $\leq 3N$ 按压扭力: $\leq 3N$ Electrical life: 500000 cycles 电气寿命: 500000 cycles mechanical: 500000 cycles 机械寿命: 500000 cycles NO reverse thrust foot torque: $\leq 30N$ NO反推脚扭力: $\leq 30N$ 													
A4				 <p>台普 ROCPCU</p>	COMMON TOLERANCE		UNIT	MM	PROJECTED		PRODUCT NAME:		
A3			X.XX		± 0.10	DRAWN BY	FUYUAN	CHECKED BY	COCO	MODEL NO: TP91201P <input type="checkbox"/> <input type="checkbox"/>			
A2			X.X		± 0.15	DATE	2019	APPROVAL B	ALEN	Https: www.rocpcu.tw			
A1			X		± 0.25	ROCPCU TECHNOLOGY CO., LTD							
REV	DATE	REVISION	DESCRIPTION		ISSUE								Copies are issued in strict confidence and shall not be reproduced or copied, or used as the basic of manufacture or sale of apparatus without permission
A		B		C		D		E		F		G	

NO 序号	Part name 部件名	Material 材料	QTY 数量	Remark 备注
10				
9				
8	Base 底座	PA66	1	Black 黑色
7	Pin 引脚	Brass 黄铜	1	gold-plating 镀金
6	Contact material 接触材质	Silvering 镀银	1	
5	Base 基座	PA66	1	Black 黑色
4	Arm nut 固定螺帽	Brass 黄铜	1	nickeling 镀镍
3	Oring O型圈	Silica gel 硅胶	1	
2	Housing 外壳	SUS/Aluminum alloy /Brass 不锈钢/铝合金/黄铜	1	
1	Key 按键	SUS/Aluminum alloy /Brass 不锈钢/铝合金/黄铜	1	

A4				 台普 ROCPCU	COMMON TOLERANCE		UNIT	MM	PROJECTED		PRODUCT NAME:
A3					X.XX	± 0.10	DRAWN BY	FUYUAN	CHECKED BY	COCO	MODEL NO: TP91201P□□
A2					X.X	± 0.15	DATE	2019	APPROVAL B	ALEN	Https: www.rocpcu.tw
A1					X	± 0.25	ROCPCU TECHNOLOGY CO.,LTD				
REV	DATE	REVISION	DESCRIPTION		ISSUE	ANGULAR					