


CIRCUIT DIAGRAM
电路图



NOTES:
 1. Rating voltage: 50mA DC12V
 1. 额定电压: 50mA DC12V
 2. Contact Resistance: ≤100mΩ Max
 2. 接触电阻: ≤100mΩ Max
 3. Insulation Resistance: ≥100MΩ
 3. 绝缘电阻: ≥100MΩ
 4. Life: 50,000 times
 4. 寿命: 50,000 times
 5. Travel: 0.20±0.1mm
 5. 行程: 0.20±0.1mm
 6. Operating Temperature: -20°C~80°C
 6. 使用温度: -20°C~80°C

Height	
32	3.2MM
35	3.5MM
38	3.8MM

TP1332 □ □ □ □
 Height
 Actuation Force
 16 : 160gf
 26 : 260gf

5	Push-button 按钮	LCP	1	Black 黑色
4	Blind flange 盖板	Brass	1	Ag plating 镀银
3	Shrapnel 弹片	SUS	2	Ag plating 镀银
2	Noumenon 本体	LCP	1	white 白色
1	Card 卡件	Brass	1	Ag plating 镀银
NO 序号	Part name 部件名	Material 材料	QTY 数量	Remark 备注

A4				
A3				
A2				
A1				
REV	DATE	REVISION	DESCRIPTION	ISSUE



COMMON TOLERANCE	
X.XX	± 0.10
X.X	± 0.15
X	± 0.25
ANGULAR	—

UNIT	MM	PROJECTED	PRODUCT NAME: TP1332 □ □ □ □
DRAWN BY	SHUHAO	CHECKED BY	COCO
DATE	2019	APPROVAL B	ALEN
MODEL NO:		Https: www.rocpcu.tw	
ROCPU TECHNOLOGY CO.,LTD			
Copies are issued in strict confidence and shall not be reproduced or copied, or used as the basic of manufacture or sale of apparatus without permission			