



1. Rating: AC 250V 3a \ AC 125av 6A
1. 额定值: AC 250V 3A \ AC 125AV 6A
2. Contact resistance:  $\leq 100\text{m}\Omega$  Max
2. 接触电阻:  $\leq 100\text{m}\Omega$  Max
3. Insulation resistance:  $\geq 100\text{m}\Omega$  Max
3. 绝缘电阻:  $\geq 100\text{m}\Omega$  Max
4. Voltage resistance: AC 500V 1 min
4. 耐电压: AC 500V 1 min
5. Temperature used:  $-16^\circ\text{C}$  to  $+60^\circ\text{C}$
5. 使用温度:  $-16^\circ\text{C}$  ~  $+60^\circ\text{C}$
6. Contact type: 1P2T
6. 接触型式: 1P2T
7. Service life: 5000 times
7. 使用寿命: 5000次
8. Operation force:  $300 \pm 100$  GF
8. 操作力:  $300 \pm 100\text{gf}$

5	Spring 弹簧	Carbon steel wire 碳钢线	1	
4	Shrapnel 弹片	BRASS 黄铜	1	Ag plating 镀银
3	Base 底座	PA66	1	Black 黑色
2	Terminal 端子	BRASS 黄铜	3	Ag plating 镀银
1	Handle 手柄	PA66	1	Black 黑色
NO 序号	Part name 部件名	Material 材料	QTY 数量	Remark 备注

A4					 <b>台普</b> <b>ROCPCU</b>	COMMON TOLERANCE	UNIT	MM	PROJECTED		PRODUCT NAME:	
A3						X.XX	$\pm 0.10$	DRAWN BY	FUYUAN	CHECKED BY	COCO	MODEL NO: TP60212025
A2						X.X	$\pm 0.15$	DATE	2019	APPROVAL B	ALEN	Https: www.rocpcu.tw
A1						X	$\pm 0.25$	<b>ROCPCU TECHNOLOGY CO.,LTD</b>				
REV	DATE	REVISION	DESCRIPTION	ISSUE		ANGULAR	—					
	A		B		C		D	E	F		G	