



| | | | | | | | | | | | |
|-----|------|----------|-------------|---|--|-------|---|-----------|---|---------------|---|
| A4 | | | |  台普 ROCPCU | COMMON TOLERANCE X.XX ± 0.10 X.X ± 0.15 X ± 0.25 ANGULAR — | UNIT | MM | PROJECTED |  | PRODUCT NAME: | |
| A3 | | | | | | | DRAWN BY | FUYUAN | CHECKED BY | COCO | MODEL NO: TP90801P <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> |
| A2 | | | | | | | DATE | 2019 | APPROVAL B | ALEN | Https: www.rocpcu.tw |
| A1 | | | | | | | ROCPCU TECHNOLOGY CO.,LTD | | | | |
| REV | DATE | REVISION | DESCRIPTION | | | ISSUE | Copies are issued in strict confidence and shall not be reproduced or copied, or used as the basic of manufacture or sale of apparatus without permission | | | | |

TP90801P

LED voltage

- 3: 3V
- 6: 6V
- 12: 12V
- 24: 24V
- 36: 36V
- 48: 48V
- 60: 60V
- 110: 110V
- 220: 220V

Material

- A: Aluminum alloy
- S: Stainless steel
- B: Brass



LED Color

- R:Red
- Y:Yellow
- G:Green
- B:Blue
- W:White
- O:Orange

性能参数



1. Insulation resistance: $\geq 1000M\Omega$
绝缘电阻 : $\geq 1000M\Omega$
2. Contact stroke: $1.50mm \pm 0.10$
接触行程 : $1.50mm \pm 0.10$
3. welding temperature: $320\text{ }^\circ\text{C} \pm 20\text{ }^\circ\text{C}$
焊接温度 : $320\text{ }^\circ\text{C} \pm 20\text{ }^\circ\text{C}$
4. Welding duration: Less than 3 seconds in duration
焊接时长: Less than 3 seconds in duration
5. Nut assembly torque: 5-14N
螺帽装配力矩: 5-14N

6. Protection level: IP65
防护等级: IP65
7. Explosion prevention level: IK08
防暴等级: IK08
8. Working environment temperature: $-20\text{ }^\circ\text{C} \sim +55\text{ }^\circ\text{C}$
工作环境温度: $-20\text{ }^\circ\text{C} \sim +55\text{ }^\circ\text{C}$
9. LED lamp power consumption: 20m以下
LED灯功耗: 20m以下
10. LED lamp lifespan: 40000h
LED寿命: 40000h
11. LED foot reverse thrust: $\leq 20N$
LED脚反推扭力: $\leq 20N$

| | | | | | | | | | | | |
|-----|------|----------|-------------|---|------------------|------------|----------------------------------|--------|------------|---|---|
| A4 | | | |  台普 ROCPCU | COMMON TOLERANCE | | UNIT | MM | PROJECTED |  | PRODUCT NAME: |
| A3 | | | | | X.XX | ± 0.10 | DRAWN BY | FUYUAN | CHECKED BY | COCO | MODEL NO: TP90801P <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> |
| A2 | | | | | X.X | ± 0.15 | DATE | 2019 | APPROVAL B | ALEN | Https: www.rocpcu.tw |
| A1 | | | | | X | ± 0.25 | ROCPCU TECHNOLOGY CO.,LTD | | | | |
| REV | DATE | REVISION | DESCRIPTION | | ISSUE | ANGULAR | | | | | |
| | A | | B | | C | | D | E | F | G | |

| NO 序号 | Part name 部件名 | Material 材料 | QTY 数量 | Remark 备注 |
|----------|----------------------|--|-----------|-------------------------|
| 1 | luminous zone 发光区 | PC 塑料 | 1 | |
| 2 | Housing 外壳 | SUS/Aluminum alloy/Brass 不锈钢/铝合金/黄铜 | 1 | Oxidized/Black 氧化/黑色 |
| 3 | Oring O型圈 | Silica gel 硅胶 | 1 | |
| 4 | Arm nut 固定螺帽 | Brass 黄铜 | 1 | nickeling 镀镍 |
| 5 | Base 基座 | PBT | 1 | |
| 6 | LEDpin LED脚 | Brass 黄铜 | 1 | Silvering 镀银 |
| 7 | | | | |
| 8 | | | | |
| 9 | | | | |
| 10 | | | | |

材质参数

| | | | | | | | | | | | |
|-----|------|----------|-------------|--|------------------|---------|----------------------------------|--------|------------|---|------------------------|
| A4 | | | |  ROCPCU | COMMON TOLERANCE | | UNIT | MM | PROJECTED |  | PRODUCT NAME: |
| A3 | | | | | X.XX | ± 0.10 | DRAWN BY | FUYUAN | CHECKED BY | COCO | MODEL NO: TP90801P□□□□ |
| A2 | | | | | X.X | ± 0.15 | DATE | 2019 | APPROVAL B | ALEN | Https: www.rocpcu.tw |
| A1 | | | | | X | ± 0.25 | ROCPCU TECHNOLOGY CO.,LTD | | | | |
| REV | DATE | REVISION | DESCRIPTION | | ISSUE | ANGULAR | | | | | |