





PCB.WELDING DRAWING
PCB.焊接图



CIRCUIT DIAGRAM
电路图



The Main Thchnology Performance
主要技术参数 性能
1.Rate voltage.current:50mA DC12V
1.额定电流.电压: 50mA DC12V
2.Contact resistance:≤100mΩ
2.接触电阻: ≤100mΩ
3.Insulated resistance:≥100MΩ
3.绝缘电阻: ≥100MΩ

4.Dielectric strength:≥250V AC/1min
4.介电强度: ≥250V AC/1min
5.Travel: 0.20±0.10mm
5.行程: 0.20±0.10mm
6.working temperature: -20℃~ + 80℃
6.工作温度: -20℃~ + 80℃
7.Service life: 200000 times
7.使用寿命: 200000次

TP1131

Height
Actuation Force
16 : 160gf
26 : 260gf
35 : 350gf

Height	
35	3.5MM
38	3.8MM
40	4.0MM
43	4.3MM
45	4.5MM
48	4.8MM
50	5.0MM
55	5.5MM
60	6.0MM
65	6.5MM
70	7.0MM
75	7.5MM
80	8.0MM
85	8.5MM
90	9.0MM
95	9.5MM
100	10.0MM

NO 序号	Part name 部件名	Material 材料	QTY 数量	Remark 备注
5	Press handle 按柄	PPA	1	Black 黑色
4	blind flange 盖板	Brass	1	Copper tin plating 镀铜锡
3	Shrapnel 弹片	SUS	1	Ag plating 镀银
2	Pedestal 基座	PPA	1	Black 黑色
1	Terminal 端子	Brass	1	Ag plating 镀银

A4				
A3				
A2				
A1				
REV	DATE	REVISION	DESCRIPTION	ISSUE



COMMON TOLERANCE	
X.XX	± 0.10
X.X	± 0.15
X	± 0.25
ANGULAR	—

UNIT	MM	PROJECTED	
DRAWN BY	SHUHAO	CHECKED BY	COCO
DATE	2019	APPROVAL B	ALEN

PRODUCT NAME: TP1131

MODEL NO:

Https: www.rocpcu.tw

ROCPCU TECHNOLOGY CO.,LTD

Copies are issued in strict confidence and shall not be reproduced or copied, or used as the basic of manufacture or sale of apparatus without permission