





A4				 台普 ROCPCU	COMMON TOLERANCE X.XX ± 0.10 X.X ± 0.15 X ± 0.25 ANGULAR —	UNIT	MM	PROJECTED		PRODUCT NAME:	
A3			DRAWN BY			SHUHAO	CHECKED BY	COCO	MODEL NO: TP91964P□□□□		
A2			DATE			2019	APPROVAL B	ALEN	Https: www.rocpcu.tw		
A1			ROCPCU TECHNOLOGY CO., LTD								
REV	DATE	REVISION	DESCRIPTION			ISSUE	Copies are issued in strict confidence and shall not be reproduced or copied, or used as the basic of manufacture or sale of apparatus without permission				

	A	B	C	D	E	F	G			
1	TP91964P <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>									
2	Operation method 1:Self-locking 2:Self-compound	LED voltage 3: 3V 6: 6V 12: 12V 24: 24V 36: 36V 48: 48V 60: 60V 110: 110V 220: 220V	Material A: Aluminum alloy S: Stainless steel B: Brass			连接形式 1. Welding temperature of wire: 320 ± 20 °C 线材焊接温度: 320±20°C Wire welding duration: less than 3 seconds 线材焊接时长: 时长3秒以下 2. Can be used with dedicated connectors: 可配专用接插件使用: 2.1 Switch function wire: green (C) blue wire (NO) yellow wire (NC) 开关功能线材: 绿色(C) 蓝线 (NO) 黄线 (NC) 2.2 LED functional wire: red wire positive pole, black wire negative pole, LED without distinction between positive and negative poles LED功能线材: 红线正极, 黑线负极, LED不分正负极				
3			LED Color R:Red Y:Yellow G:Green B:Blue W:White O:Orange							
4			性能参数 1. Heating current: Ui: AC250V, Ith: 5A 发热电流: Ui: AC250V, Ith: 5A 2. Rated current:3A/DC36V 额定电流:3A/DC36V 3. Insulation resistance:≥1000MΩ 绝缘电阻 :≥1000MΩ 4. Contact resistance:≤50mΩ 接触电阻 :≤50mΩ 5. Pressing stroke:3.00mm ± 0.10 按压行程:3.00mm ± 0.10 6. Contact stroke:1.50mm±0.10 接触行程 :1.50mm±0.10 7. Nut assembly torque:5-14N 螺帽装配力矩:5-14N 8. Protection level:IP67 防护等级:IP67			9. Explosion prevention level: IK10 防暴等级: IK10 10. Working environment temperature: -20 °C~+55 °C 工作环境温度: -20 °C~+55 °C 11. Compression torque: ≤ 4N 按压扭力: ≤4N 12. Electrical life: 50000 cycles 电气寿命: 50000 cycles 13. mechanical: 500000cycles 机械寿命: 500000cycles 14. NO reverse thrust foot torque: ≤30N NO反推脚扭力: ≤30N 15. LED lamp power consumption: 20m以下 LED灯功耗: 20m以下 16. LED lamp lifespan: 40000h LED寿命: 40000h				
5	A4									
	A3									
	A2									
	A1									
	REV	DATE	REVISION DESCRIPTION	ISSUE						
					COMMON TOLERANCE	UNIT	MM	PROJECTED		PRODUCT NAME:
					X.XX ± 0.10	DRAWN BY	SHUHAO	CHECKED BY	COCO	MODEL NO: TP91964P <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>
					X.X ± 0.15	DATE	2019	APPROVAL B	ALEN	Https: www.rocpcu.tw
					X ± 0.25	ROCPCU TECHNOLOGY CO.,LTD				
					ANGULAR	Copies are issued in strict confidence and shall not be reproduced or copied, or used as the basic of manufacture or sale of apparatus without permission				
	A	B	C	D	E	F	G			

