







A4					 <b>台普</b> <b>ROCPCU</b>	COMMON TOLERANCE		UNIT	MM	PROJECTED		PRODUCT NAME:	
A3						X.XX	± 0.10	DRAWN BY	SHUHAO	CHECKED BY	COCO	MODEL NO: TP91642G□□□□	
A2						X.X	± 0.15	DATE	2019	APPROVAL	B	ALEN	Https: www.rocpcu.tw
A1						X	± 0.25	<h1>ROCPCU TECHNOLOGY CO.,LTD</h1>					
REV	DATE	REVISION	DESCRIPTION	ISSUE		ANGULAR	—						<small>Copies are issued in strict confidence and shall not be reproduced or copied, or used as the basic of manufacture or sale of apparatus without permission</small>

	A	B	C	D	E	F	G			
1	<p style="text-align: center;"><b>TP91642G</b> □ □ □ □</p> <div style="display: flex; justify-content: space-between;"> <div style="width: 30%;"> <p><b>Operation method</b></p> <p>1:Self-locking 2:Self-compound</p> </div> <div style="width: 30%;"> <p><b>Material</b></p> <p>A: Aluminum alloy S: Stainless steel B: Brass</p> </div> <div style="width: 30%;"> <p><b>LED voltage</b></p> <p>3: 3V 6: 6V 12: 12V 24: 24V 36: 36V 48: 48V 60: 60V 110: 110V 220: 220V</p> </div> <div style="width: 30%;"> <p><b>LED Color</b></p> <p>R:Red Y:Yellow G:Green B:Blue W:White O:Orange</p> </div> </div>									
2										
3	<p><b>性能参数</b></p> <div style="display: flex; justify-content: space-between;"> <div style="width: 48%;"> <ol style="list-style-type: none"> <li>Heating current: Ui: AC250V, Ith: 3A 发热电流: Ui: AC250V, Ith: 3A</li> <li>Rated current:2A/DC36V 额定电流:2A/DC36V</li> <li>Insulation resistance:≥1000MΩ 绝缘电阻 :≥1000MΩ</li> <li>Contact resistance:≤50mΩ 接触电阻 :≤50mΩ</li> <li>Pressing stroke:2.80mm ± 0.10 按压行程:2.80mm ± 0.10</li> <li>Contact stroke:1.10mm±0.10 接触行程 :1.10mm±0.10</li> <li>Nut assembly torque:5-14N 螺帽装配力矩:5-14N</li> <li>Protection level:IP67 防护等级:IP67</li> </ol> </div> <div style="width: 48%;"> <ol style="list-style-type: none"> <li>Explosion prevention level: IK09 防暴等级: IK09</li> <li>Working environment temperature: -20 °C~+55 °C 工作环境温度: -20 °C~+55 °C</li> <li>Compression torque: ≤ 3N 按压扭力: ≤3N</li> <li>Electrical life: 500000 cycles 电气寿命: 500000 cycles</li> <li>mechanical: 500000cycles 机械寿命: 500000cycles</li> <li>NO reverse thrust foot torque: ≤30N NO反推脚扭力: ≤30N</li> <li>LED lamp power consumption: 20m以下 LED灯功耗: 20m以下</li> <li>LED lamp lifespan: 40000h LED寿命: 40000h</li> </ol> </div> </div>									
4										
5	A4				UNIT	MM	PROJECTED		PRODUCT NAME:	
	A3			 <b>ROCPCU</b>	COMMON TOLERANCE					
	A2				X.XX	± 0.10	DRAWN BY	SHUHAO	CHECKED BY	COCO
	A1				X.X	± 0.15	DATE	2019	APPROVAL B	ALEN
	REV	DATE	REVISION DESCRIPTION	ISSUE	X	± 0.25	<b>ROCPCU TECHNOLOGY CO.,LTD</b>			
					ANGULAR	—	Copies are issued in strict confidence and shall not be reproduced or copied, or used as the basic of manufacture or sale of apparatus without permission			
	A	B	C	D	E	F	G			

NO 序号	Part name 部件名	Material 材料	QTY 数量	Remark 备注
1	Key 按键	SUS/Aluminum alloy/Brass 不锈钢/铝合金/黄铜	1	
2	Housing 外壳	SUS/Aluminum alloy/Brass 不锈钢/铝合金/黄铜	1	
3	Oring O型圈	Silica gel 硅胶	1	
4	Arm nut 固定螺帽	Brass 黄铜	1	nickeling 镀镍
5	Base 基座	PA66	1	Black 黑色
6	Contact material 接触材质	Silvering 镀银	1	
7	Pin 引脚	Brass 黄铜	1	gold-plating 镀金
8	LEDpin LED脚	Brass 黄铜	1	Silvering 镀银
9	luminous zone 发光区	PC 塑料	1	

A4				 <b>ROCPCU</b>	COMMON TOLERANCE		UNIT	MM	PROJECTED		PRODUCT NAME:
A3					X.XX	± 0.10	DRAWN BY	SHUHAO	CHECKED BY	COCO	MODEL NO: TP91642G□□□□
A2					X.X	± 0.15	DATE	2019	APPROVAL B	ALEN	Https: www.rocpcu.tw
A1					X	± 0.25	<b>ROCPCU TECHNOLOGY CO.,LTD</b>				
REV	DATE	REVISION	DESCRIPTION		ISSUE	ANGULAR					