



Product specification:  
 产品规格:  
 Rated current: 50mA MAX  
 额定电流: 50mA MAX  
 Rated voltage: DC 12V  
 额定电压: DC 12V  
 Contact resistance: ≤ 70mΩ  
 接触电阻: ≤70mΩ  
 Insulation resistance: ≥ 100MΩ  
 绝缘电阻: ≥100MΩ

Compressive strength: AC250V 50Hz/1 min  
 耐压强度: AC250V 50Hz/1 min  
 Operating force: 180 ± 50gf  
 操作力度: 180±50gf  
 Mechanical life: 10000 cycles  
 机械寿命: 10000 cycles  
 Operating stroke: 1.5 ± 0.2mm  
 操作行程: 1.5±0.2mm  
 Operating temperature: -25 °C to +70 °C  
 使用温度: -25°C to +70°C

6	Shrapnel 弹片	SUS	1	
5	Cover 盖板	Phosphor copper 磷铜	1	Ag plating 镀银
4	Reed 簧片	Brass 黄铜	1	Ag plating 镀银
3	Handle 手柄	PA46	1	Black 黑色
2	Terminal 端子	Phosphor copper 磷铜	1	Ag plating 镀银
1	Base 基座	LCP	1	Black 黑色
NO 序号	Part name 部件名	Material 材料	QTY 数量	Remark 备注

A4				
A3				
A2				
A1				
REV	DATE	REVISION	DESCRIPTION	ISSUE



COMMON TOLERANCE	
X.XX	± 0.10
X.X	± 0.15
X	± 0.25
ANGULAR	—

UNIT	MM	PROJECTED	PRODUCT NAME:
DRAWN BY	FUYUAN	CHECKED BY	COCO
DATE	2019	APPROVAL B	ALEN
MODEL NO: TP607221315			
Https: www.rocpu.tw			
<b>ROCPCU TECHNOLOGY CO.,LTD</b>			
Copies are issued in strict confidence and shall not be reproduced or copied, or used as the basic of manufacture or sale of apparatus without permission			