



Specifications

CONTACT RATING: 0.1A @ 30 VDC.
 MECHANICAL & ELECTRICAL LIFE: 50,000 cycles.
 CONTACT RESISTANCE: 150 m Ω max. initial.
 INSULATION RESISTANCE: 100 M Ω min. @ 100 VDC.
 OPERATING TEMPERATURE: -20°C to +70°C.
 DIELECTRIC STRENGTH: 100 volts AC @ 60 Hz.
 PACKAGING: Bulk.

Materials

HOUSING: P.P.S.
 ACTUATOR: PA66
 MOVABLE CONTACT: Tin bronze, silver plated.

PART NO.	H
DDS001-A	8.3
DDS001-B	8.5
DDS001-C	8.7
DDS001-D	9.3
DDS001-E	11
DDS001-F	12.3
DDS001-G	13.7



A4						UNIT	MM	PROJECTED		PRODUCT NAME:
A3						DRAWN BY	FUYUAN	CHECKED BY	COCO	MODEL NO: DDS001-X
A2						DATE	2017	APPROVAL BY	ALEN	Https: www.rocpu.tw
A1						ROC PU TECHNOLOGY CO.,LTD				
REV.	DATE	REVISION	DESCRIPTION	ISSUE	COMMON TOLERANCE:	Copies are issued in strict confidence and shall not be reproduced or copied, or used as the basic of manufacture or sale of apparatus without permission				
					X.XX	± 0.10				
					X.X	± 0.15				
					X	± 0.25				
					ANGULAR	—				